FILE NO. SVM-07009

Carrier

# SERVICE MANUAL

# AIR-CONDITIONER

## SPLIT WALL TYPE

## *42NQV025M / 38NYV025M*
## *42NQV025M-A / 38NYV025M-A*



HFC
R410A

*March, 2007*

Downloaded from AC-Manual.com Manuals

# CONTENTS

1. SAFETY PRECAUTIONS ..... 3
2. SPECIFICATIONS ..... 5
3. REFRIGERANT R410A ..... 7
4. CONSTRUCTION VIEWS ..... 15
5. WIRING DIAGRAM ..... 18
6. SPECIFICATIONS OF ELECTRICAL PARTS ..... 20
7. REFRIGERANT CYCLE DIAGRAM ..... 21
8. CONTROL BLOCK DIAGRAM ..... 25
9. OPERATION DESCRIPTION ..... 28
10. INSTALLATION PROCEDURE ..... 56
11. HOW TO DIAGNOSE THE TROUBLE ..... 58
12. PART REPLACEMENT ..... 77
13. EXPLODED VIEWS AND PARTS LIST ..... 87



Downloaded from AC-Manual.com Manuals

# 1. SAFETY PRECAUTIONS

**For general public use**

Power supply cord of outdoor unit shall be more than 1.5 $mm^2$ (H07RN-F or 60245IEC66) polychloroprene sheathed flexible cord.

- Read this “SAFETY PRECAUTIONS” carefully before servicing.
- The precautions described below include the important items regarding safety. Observe them without fail.
- After the servicing work, perform a trial operation to check for any problem.
- Turn off the main power supply switch (or breaker) before the unit maintenance.

**CAUTION**

**New Refrigerant Air Conditioner Installation**

- **THIS AIR CONDITIONER ADOPTS THE NEW HFC REFRIGERANT (R410A) WHICH DOES NOT DESTROY OZONE LAYER.**

R410A refrigerant is apt to be affected by impurities such as water, oxidizing membrane, and oils because the working pressure of R410A refrigerant is approx. 1.6 times of refrigerant R22. Accompanied with the adoption of the new refrigerant, the refrigeration machine oil has also been changed. Therefore, during installation work, be sure that water, dust, former refrigerant, or refrigeration machine oil does not enter into the new type refrigerant R410A air conditioner circuit.

To prevent mixing of refrigerant or refrigerating machine oil, the sizes of connecting sections of charging port on main unit and installation tools are different from those used for the conventional refrigerant units.

Accordingly, special tools are required for the new refrigerant (R410A) units. For connecting pipes, use new and clean piping materials with high pressure fittings made for R410A only, so that water and/or dust does not enter. Moreover, do not use the existing piping because there are some problems with pressure fittings and possible impurities in existing piping.

**CAUTION**

**TO DISCONNECT THE APPLIANCE FROM THE MAIN POWER SUPPLY**

This appliance must be connected to the main power supply by a circuit breaker or a switch with a contact separation of at least 3 mm.

**DANGER**

- **ASK AN AUTHORIZED DEALER OR QUALIFIED INSTALLATION PROFESSIONAL TO INSTALL/MAINTAIN THE AIR CONDITIONER.**

  INAPPROPRIATE SERVICING MAY RESULT IN WATER LEAKAGE, ELECTRIC SHOCK OR FIRE.
- TURN OFF MAIN POWER SUPPLY BEFORE ATTEMPTING ANY ELECTRICAL WORK. MAKE SURE ALL POWER SWITCHES ARE OFF. FAILURE TO DO SO MAY CAUSE ELECTRIC SHOCK.

**⚠ DANGER: HIGH VOLTAGE**

The high voltage circuit is incorporated.

Be careful to do the check service, as the electric shock may be caused in case of touching parts on the P.C. board by hand.

- CORRECTLY CONNECT THE CONNECTING CABLE. IF THE CONNECTING CABLE IS INCORRECTLY CONNECTED, ELECTRIC PARTS MAY BE DAMAGED.
- CHECK THAT THE EARTH WIRE IS NOT BROKEN OR DISCONNECTED BEFORE SERVICE AND INSTALLATION. FAILURE TO DO SO MAY CAUSE ELECTRIC SHOCK.



Downloaded from AC-Manual.com Manuals

- DO NOT INSTALL NEAR CONCENTRATIONS OF COMBUSTIBLE GAS OR GAS VAPORS. FAILURE TO FOLLOW THIS INSTRUCTION CAN RESULT IN FIRE OR EXPLOSION.
- TO PREVENT THE INDOOR UNIT FROM OVERHEATING AND CAUSING A FIRE HAZARD, PLACE THE UNIT WELL AWAY (MORE THAN 2 M) FROM HEAT SOURCES SUCH AS RADIATORS, HEAT REGISTORS, FURNACE, STOVES, ETC.
- WHEN MOVING THE AIR-CONDITIONER FOR INSTALLATION IN ANOTHER PLACE, BE VERY CAREFUL NOT TO ALLOW THE SPECIFIED REFRIGERANT (R410A) TO BECOME MIXED WITH ANY OTHER GASEOUS BODY INTO THE REFRIGERATION CIRCUIT. IF AIR OR ANY OTHER GAS IS MIXED IN THE REFRIGERANT, THE GAS PRESSURE IN THE REFRIGERATION CIRCUIT WILL BECOME ABNORMALLY HIGH AND IT MAY RESULT IN THE PIPE BURSTING AND POSSIBLE PERSONNEL INJURIES.
- IN THE EVENT THAT THE REFRIGERANT GAS LEAKS OUT OF THE PIPE DURING THE SERVICE WORK AND THE INSTALLATION WORK, IMMEDIATELY LET FRESH AIR INTO THE ROOM. IF THE REFRIGERANT GAS IS HEATED, SUCH AS BY FIRE, GENERATION OF POISONOUS GAS MAY RESULT.

## WARNING

- **Never modify this unit by removing any of the safety guards or bypass any of the safety interlock switches.**
- **Do not install in a place which cannot bear the weight of the unit. Personal injury and property damage can result if the unit falls.**
- **After the installation work, confirm that refrigerant gas does not leak.**
  If refrigerant gas leaks into the room and flows near a fire source, such as a cooking range, noxious gas may generate.
- **The electrical work must be performed by a qualified electrician in accordance with the Installation Manual. Make sure the air conditioner uses an exclusive circuit.**
  An insufficient circuit capacity or inappropriate installation may cause fire.
- **When wiring, use the specified cables and connect the terminals securely to prevent external forces applied to the cable from affecting the terminals.**
- **Be sure to provide grounding.**
  Do not connect ground wires to gas pipes, water pipes, lightning rods or ground wires for telephone cables.
- **Conform to the regulations of the local electric company when wiring the power supply.**
  Inappropriate grounding may cause electric shock.

## CAUTION

- Exposure of unit to water or other moisture before installation may result in an electrical short. Do not store in a wet basement or expose to rain or water.
- Do not install in a place that can increase the vibration of the unit. Do not install in a place that can amplify the noise level of the unit or where noise or discharged air might disturb neighbors.
- To avoid personal injury, be careful when handling parts with sharp edges.
- **Perform the specified installation work to guard against an earthquake.**
  If the air conditioner is not installed appropriately, accidents may occur due to the falling unit.

**For Reference:**

If a heating operation would be continuously performed for a long time under the condition that the outdoor temperature is 0°C or lower, drainage of defrosted water may be difficult due to freezing of the bottom plate, resulting in a trouble of the cabinet or fan.

It is recommended to procure an antifreeze heater locally for a safe installation of the air conditioner.

For details, contact the dealer.



Downloaded from AC-Manual.com Manuals

# 1. SPECIFICATIONS

## 1-1. Specifications

| | | | | | | |
|---|---|---|---|---|---|---|
| Unit model | Indoor | | | | **42NQV025M, 42NQV025M-A** | |
| | Outdoor | | | | **38NYV025M, 38NYV025M-A** | |
| Cooling capacity | | | | (kW) | 2.5 | |
| Cooling capacity range | | | | (kW) | 1.1 - 2.9 | |
| Heating capacity | | | | (kW) | 3.2 | |
| Heating capacity range | | | | (kW) | 0.9 - 4.0 | |
| Power supply | | | | | 1Ph/50Hz/220-240V | |
| Electric characteristic | Indoor | Operation mode | | | **Cooling** | **Heating** |
| | | Running current | | (A) | 0.16 - 0.14 | 0.16 - 0.14 |
| | | Power consumption | | (W) | 30 | 30 |
| | | Power factor | | (%) | 87 | 87 |
| | Outdoor | Operation mode | | | **Cooling** | **Heating** |
| | | Running current | | (A) | 3.54 - 3.25 | 4.09 - 3.76 |
| | | Power consumption | | (W) | 740 | 855 |
| | | Power factor | | (%) | 95 | 95 |
| | | Starting current | | (A) | 4.25 - 3.90 | |
| COP (Cooling / Heating) | | | | | 3.25/3.62 | |
| Operating noise | Indoor | High | (Cooling / Heating) | (dB-A) | 39/41 | |
| | | Medium | (Cooling / Heating) | (dB-A) | 34/36 | |
| | | Low | (Cooling / Heating) | (dB-A) | 30/31 | |
| | Outdoor | | (Cooling / Heating) | (dB-A) | 48/50 | |
| Indoor unit | Unit model | | | | **42NQV025M, 42NQV025M-A** | |
| | Dimension | Height | | (mm) | 250 | |
| | | Width | | (mm) | 740 | |
| | | Depth | | (mm) | 195 | |
| | Net weight | | | (kg) | 8 | |
| | Fan motor output | | | (W) | 20 | |
| | Air flow rate | | (Cooling / Heating) | ($m^3$ / min) | 8.7/9.6 | |
| Outdoor unit | Unit model | | | | **38NYV025M, 38NYV025M-A** | |
| | Dimension | Height | | (mm) | 530 | |
| | | Width | | (mm) | 660 | |
| | | Depth | | (mm) | 240 | |
| | Net weight | | | (kg) | 29 | |
| | Compressor | Motor output | | (W) | 750 | |
| | | Type | | | Single rotary type with DC-inverter variable speed control | |
| | | Model | | | DA89X1C-23FZ | |
| | Fan motor output | | | (W) | 20 | |
| | Air flow rate | | (Cooling / Heating) | ($m^3$ / min) | 27/27 | |
| Piping connection | Type | | | | Flare connection | |
| | Indoor unit | Liquid side | | (mm) | ∅6.35 | |
| | | Gas side | | (mm) | ∅9.52 | |
| | Outdoor unit | Liquid side | | (mm) | ∅6.35 | |
| | | Gas side | | (mm) | ∅9.52 | |
| | Maximum length | | | (m) | 10 | |
| | Maximun charge-less length | | | (m) | 10 | |
| | Maximum height difference | | | (m) | 8 | |
| Refrigerant | Name of refrigerant | | | | R410A | |
| | Weight | | | (kg) | 0.63 | |
| Wiring connection | | Power supply | | | 3 Wires: Includes earth (Outdoor) | |
| | | Interconnection | | | 4 Wires: Includes earth | |
| Usable temperature range | | Indoor | (Cooling / Heating) | (°C) | 21 - 32/Up to 27 | |
| | | Outdoor | (Cooling / Heating) | (°C) | 15 - 43/-10 - 24 | |
| Accessory | Indoor unit | Installation plate | | | 1 | |
| | | Wireless remote controller | | | 1 | |
| | | batteries | | | 2 | |
| | | Remote controller holder | | | 1 | |
| | | Nano-Photo Copper Zinc filter | | | 1 | |
| | | Nono-Silver Ginseng filter | | | 1 | |
| | | Mounting screw | | | 6 (∅4 x 25L) | |
| | | Pan head wood screw | | | 2 (∅3.1 x 16L) | |
| | | Plasma air purifier | | | - | |
| | | Installation manual | | | 1 | |
| | | Owner's manual | | | 1 | |
| | Outdoor unit | Drain nipple | | | 1 | |
| | | Water proof rubber cap | | | - | |

* The specification may be subject to change without notice for purpose of improvement.

Downloaded from AC-Manual.com Manuals

## 2-2. Operation Characteristic Curve

### 42NQV025M, 42NQV025M-A

<Cooling>




<Heating>




## 2-3. Capacity Variation Ratio According to Temperature

### 42NQV025M, 42NQV025M-A

<Cooling>




<Heating>






Downloaded from AC-Manual.com Manuals

# 3. REFRIGERANT R410A

This air conditioner adopts the new refrigerant HFC (R410A) which does not damage the ozone layer.

The working pressure of the new refrigerant R410A is 1.6 times higher than conventional refrigerant (R22). The refrigerating oil is also changed in accordance with change of refrigerant, so be careful that water, dust, and existing refrigerant or refrigerating oil are not entered in the refrigerant cycle of the air conditioner using the new refrigerant during installation work or servicing time.

The next section describes the precautions for air conditioner using the new refrigerant. Conforming to contents of the next section together with the general cautions included in this manual, perform the correct and safe work.

## 3-1. Safety During Installation/Servicing

As R410A's pressure is about 1.6 times higher than that of R22, improper installation/servicing may cause a serious trouble. By using tools and materials exclusive for R410A, it is necessary to carry out installation/servicing safely while taking the following precautions into consideration.

1. Never use refrigerant other than R410A in an air conditioner which is designed to operate with R410A.

   If other refrigerant than R410A is mixed, pressure in the refrigeration cycle becomes abnormally high, and it may cause personal injury, etc. by a rupture.
2. Confirm the used refrigerant name, and use tools and materials exclusive for the refrigerant R410A.

   The refrigerant name R410A is indicated on the visible place of the outdoor unit of the air conditioner using R410A as refrigerant. To prevent mischarging, the diameter of the service port differs from that of R22.
3. If a refrigeration gas leakage occurs during installation/servicing, be sure to ventilate fully.

   If the refrigerant gas comes into contact with fire, a poisonous gas may occur.
4. When installing or removing an air conditioner, do not allow air or moisture to remain in the refrigeration cycle. Otherwise, pressure in the refrigeration cycle may become abnormally high so that a rupture or personal injury may be caused.
5. After completion of installation work, check to make sure that there is no refrigeration gas leakage.

   If the refrigerant gas leaks into the room, coming into contact with fire in the fan-driven heater, space heater, etc., a poisonous gas may occur.
6. When an air conditioning system charged with a large volume of refrigerant is installed in a small room, it is necessary to exercise care so that, even when refrigerant leaks, its concentration does not exceed the marginal level.

   If the refrigerant gas leakage occurs and its concentration exceeds the marginal level, an oxygen starvation accident may result.
7. Be sure to carry out installation or removal according to the installation manual.

   Improper installation may cause refrigeration trouble, water leakage, electric shock, fire, etc.
8. Unauthorized modifications to the air conditioner may be dangerous. If a breakdown occurs please call a qualified air conditioner technician or electrician.

   Improper repair's may result in water leakage, electric shock and fire, etc.

## 3-2. Refrigerant Piping Installation

### 3-2-1. Piping Materials and Joints Used

For the refrigerant piping installation, copper pipes and joints are mainly used. Copper pipes and joints suitable for the refrigerant must be chosen and installed. Furthermore, it is necessary to use clean copper pipes and joints whose interior surfaces are less affected by contaminants.

**1. Copper Pipes**

It is necessary to use seamless copper pipes which are made of either copper or copper alloy and it is desirable that the amount of residual oil is less than 40 mg/10 m. Do not use copper pipes having a collapsed, deformed or discolored portion (especially on the interior surface).

Otherwise, the expansion valve or capillary tube may become blocked with contaminants.

As an air conditioner using R410A incurs pressure higher than when using R22, it is necessary to choose adequate materials.

Thicknesses of copper pipes used with R410A are as shown in Table 3-2-1. Never use copper pipes thinner than 0.8 mm even when it is available on the market.



Downloaded from AC-Manual.com Manuals

**Table 3-2-1 Thicknesses of annealed copper pipes**

| | | Thickness (mm) | |
|---|---|---|---|
| **Nominal diameter** | **Outer diameter (mm)** | **R410A** | R22 |
| 1/4 | 6.35 | 0.80 | 0.80 |
| 3/8 | 9.52 | 0.80 | 0.80 |
| 1/2 | 12.70 | 0.80 | 0.80 |
| 5/8 | 15.88 | 1.00 | 1.00 |

### 2. Joints

For copper pipes, flare joints or socket joints are used. Prior to use, be sure to remove all contaminants.

a) Flare Joints

Flare joints used to connect the copper pipes cannot be used for pipings whose outer diameter exceeds 20 mm. In such a case, socket joints can be used.

Sizes of flare pipe ends, flare joint ends and flare nuts are as shown in Tables 3-2-3 to 3-2-6 below.

b) Socket Joints

Socket joints are such that they are brazed for connections, and used mainly for thick pipings whose diameter is larger than 20 mm.

Thicknesses of socket joints are as shown in Table 3-2-2.

**Table 3-2-2 Minimum thicknesses of socket joints**

| Nominal diameter | Reference outer diameter of copper pipe jointed (mm) | Minimum joint thickness (mm) |
|---|---|---|
| 1/4 | 6.35 | 0.50 |
| 3/8 | 9.52 | 0.60 |
| 1/2 | 12.70 | 0.70 |
| 5/8 | 15.88 | 0.80 |

## 3-2-2. Processing of Piping Materials

When performing the refrigerant piping installation, care should be taken to ensure that water or dust does not enter the pipe interior, that no other oil than lubricating oils used in the installed air-water heat pump is used, and that refrigerant does not leak. When using lubricating oils in the piping processing, use such lubricating oils whose water content has been removed. When stored, be sure to seal the container with an airtight cap or any other cover.

### 1. Flare processing procedures and precautions

a) Cutting the Pipe

By means of a pipe cutter, slowly cut the pipe so that it is not deformed.

b) Removing Burrs and Chips

If the flared section has chips or burrs, refrigerant leakage may occur.
Carefully remove all burrs and clean the cut surface before installation.

c) Insertion of Flare Nut



Downloaded from AC-Manual.com Manuals

d) Flare Processing

Make certain that a clamp bar and copper pipe have been cleaned.

By means of the clamp bar, perform the flare processing correctly.

Use either a flare tool for R410A or conventional flare tool.

Flare processing dimensions differ according to the type of flare tool. When using a conventional flare tool, be sure to secure “dimension A” by using a gauge for size adjustment.




**Fig. 3-2-1 Flare processing dimensions**

**Table 3-2-3 Dimensions related to flare processing for R410A**

| Nominal diameter | Outer diameter (mm) | Thickness (mm) | A (mm) | | |
|---|---|---|---|---|---|
| | | | Flare tool for R410A clutch type | Conventional flare tool | |
| | | | | Clutch type | Wing nut type |
| 1/4 | 6.35 | 0.8 | 0 to 0.5 | 1.0 to 1.5 | 1.5 to 2.0 |
| 3/8 | 9.52 | 0.8 | 0 to 0.5 | 1.0 to 1.5 | 1.5 to 2.0 |
| 1/2 | 12.70 | 0.8 | 0 to 0.5 | 1.0 to 1.5 | 2.0 to 2.5 |
| 5/8 | 15.88 | 1.0 | 0 to 0.5 | 1.0 to 1.5 | 2.0 to 2.5 |

**Table 3-2-4 Dimensions related to flare processing for R22**

| Nominal diameter | Outer diameter (mm) | Thickness (mm) | A (mm) | | |
|---|---|---|---|---|---|
| | | | Flare tool for R22 clutch type | Conventional flare tool | |
| | | | | Clutch type | Wing nut type |
| 1/4 | 6.35 | 0.8 | 0 to 0.5 | 0.5 to 1.0 | 1.0 to 1.5 |
| 3/8 | 9.52 | 0.8 | 0 to 0.5 | 0.5 to 1.0 | 1.0 to 1.5 |
| 1/2 | 12.70 | 0.8 | 0 to 0.5 | 0.5 to 1.0 | 1.5 to 2.0 |
| 5/8 | 15.88 | 1.0 | 0 to 0.5 | 0.5 to 1.0 | 1.5 to 2.0 |

**Table 3-2-5 Flare and flare nut dimensions for R410A**

| Nominal diameter | Outer diameter (mm) | Thickness (mm) | Dimension (mm) | | | | Flare nut width (mm) |
|---|---|---|---|---|---|---|---|
| | | | A | B | C | D | |
| 1/4 | 6.35 | 0.8 | 9.1 | 9.2 | 6.5 | 13 | 17 |
| 3/8 | 9.52 | 0.8 | 13.2 | 13.5 | 9.7 | 20 | 22 |
| 1/2 | 12.70 | 0.8 | 16.6 | 16.0 | 12.9 | 23 | 26 |
| 5/8 | 15.88 | 1.0 | 19.7 | 19.0 | 16.0 | 25 | 29 |



Downloaded from AC-Manual.com Manuals

**Table 3-2-6 Flare and flare nut dimensions for R22**

| Nominal diameter | Outer diameter (mm) | Thickness (mm) | Dimension (mm) | | | | Flare nut width (mm) |
|---|---|---|---|---|---|---|---|
| | | | A | B | C | D | |
| 1/4 | 6.35 | 0.8 | 9.0 | 9.2 | 6.5 | 13 | 17 |
| 3/8 | 9.52 | 0.8 | 13.0 | 13.5 | 9.7 | 20 | 22 |
| 1/2 | 12.70 | 0.8 | 16.2 | 16.0 | 12.9 | 20 | 24 |
| 5/8 | 15.88 | 1.0 | 19.7 | 19.0 | 16.0 | 23 | 27 |
| 3/4 | 19.05 | 1.0 | 23.3 | 24.0 | 19.2 | 34 | 36 |




**Fig. 3-2-2 Relations between flare nut and flare seal surface**

## 2. Flare Connecting Procedures and Precautions

a) Make sure that the flare and union portions do not have any scar or dust, etc.

b) Correctly align the processed flare surface with the union axis.

c) Tighten the flare with designated torque by means of a torque wrench. The tightening torque for R410A is the same as that for conventional R22. Incidentally, when the torque is weak, the gas leakage may occur. When it is strong, the flare nut may crack and may be made non-removable. When choosing the tightening torque, comply with values designated by manufacturers. Table 3-2-7 shows reference values.

**NOTE :**

When applying oil to the flare surface, be sure to use oil designated by the manufacturer.
If any other oil is used, the lubricating oils may deteriorate and cause the compressor to burn out.

**Table 3-2-7 Tightening torque of flare for R410A [Reference values]**

| Nominal diameter | Outer diameter (mm) | Tightening torque N•m (kgf•cm) | Tightening torque of torque wrenches available on the market N•m (kgf•cm) |
|---|---|---|---|
| 1/4 | 6.35 | 14 to 18 (140 to 180) | 16 (160), 18 (180) |
| 3/8 | 9.52 | 33 to 42 (330 to 420) | 42 (420) |
| 1/2 | 12.70 | 50 to 62 (500 to 620) | 55 (550) |
| 5/8 | 15.88 | 63 to 77 (630 to 770) | 65 (650) |



Downloaded from AC-Manual.com Manuals

## 3-3. Tools

### 3-3-1. Required Tools

The service port diameter of packed valve of the outdoor unit in the air-water heat pump using R410A is changed to prevent mixing of other refrigerant. To reinforce the pressure-resisting strength, flare processing dimensions and opposite side dimension of flare nut (For Ø12.7 copper pipe) of the refrigerant piping are lengthened.

The used refrigerating oil is changed, and mixing of oil may cause a trouble such as generation of sludge, clogging of capillary, etc. Accordingly, the tools to be used are classified into the following three types.

1. Tools exclusive for R410A (Those which cannot be used for conventional refrigerant (R22))
2. Tools exclusive for R410A, but can be also used for conventional refrigerant (R22)
3. Tools commonly used for R410A and for conventional refrigerant (R22)

The table below shows the tools exclusive for R410A and their interchangeability.

**Tools exclusive for R410A (The following tools for R410A are required.)**

Tools whose specifications are changed for R410A and their interchangeability

| No. | Used tool | Usage | R410A air-water heat pump installation | | Conventional air-water heat pump installation |
|---|---|---|---|---|---|
| | | | Existence of new equipment for R410A | Whether conventional equipment can be used | Whether new equipment can be used with conventional refrigerant |
| 1 | Flare tool | Pipe flaring | Yes | ***(Note 1)** | ○ |
| 2 | Copper pipe gauge for adjusting projection margin | Flaring by conventional flare tool | Yes | ***(Note 1)** | ***(Note 1)** |
| 3 | Torque wrench (For Ø12.7) | Connection of flare nut | Yes | × | × |
| 4 | Gauge manifold | Evacuating, refrigerant charge, run check, etc. | Yes | × | × |
| 5 | Charge hose | | | | |
| 6 | Vacuum pump adapter | Vacuum evacuating | Yes | × | ○ |
| 7 | Electronic balance for refrigerant charging | Refrigerant charge | Yes | × | ○ |
| 8 | Refrigerant cylinder | Refrigerant charge | Yes | × | × |
| 9 | Leakage detector | Gas leakage check | Yes | × | ○ |
| 10 | Charging cylinder | Refrigerant charge | **(Note 2)** | × | × |

**(Note 1)** When flaring is carried out for R410A using the conventional flare tools, adjustment of projection margin is necessary. For this adjustment, a copper pipe gauge, etc. are necessary.

**(Note 2)** Charging cylinder for R410A is being currently developed.

**General tools (Conventional tools can be used.)**

In addition to the above exclusive tools, the following equipments which serve also for R22 are necessary as the general tools.

1. Vacuum pump
   Use vacuum pump by attaching vacuum pump adapter.
2. Torque wrench (For Ø6.35, Ø9.52)
3. Pipe cutter
4. Reamer
5. Pipe bender
6. Level vial
7. Screwdriver (+, –)
8. Spanner or Monkey wrench
9. Hole core drill (Ø65)
10. Hexagon wrench (Opposite side 4mm)
11. Tape measure
12. Metal saw

Also prepare the following equipments for other installation method and run check.

1. Clamp meter
2. Thermometer
3. Insulation resistance tester
4. Electroscope



Downloaded from AC-Manual.com Manuals

## 3-4. Recharging of Refrigerant

When it is necessary to recharge refrigerant, charge the specified amount of new refrigerant according to the following steps.

Recover the refrigerant, and check no refrigerant remains in the equipment.

↓

Connect the charge hose to packed valve service port at the outdoor unit's gas side.

↓

Connect the charge hose to the vacuum pump adapter.

↓

Open fully both packed valves at liquid and gas sides.

↓

Place the handle of the gauge manifold Low in the fully opened position, and turn on the vacuum pump's power switch. Then, evacuating the refrigerant in the cycle.

↓

When the compound gauge's pointer has indicated –0.1 Mpa (–76 cmHg), place the handle Low in the fully closed position, and turn off the vacuum pump's power switch.

↓

Keep the status as it is for 1 to 2 minutes, and ensure that the compound gauge's pointer does not return.

↓

Set the refrigerant cylinder to the electronic balance, connect the connecting hose to the cylinder and the connecting port of the electronic balance, and charge **liquid refrigerant**.

(For refrigerant charging, see the figure below.)

1. Never charge refrigerant exceeding the specified amount.
2. If the specified amount of refrigerant cannot be charged, charge refrigerant **bit by bit** in COOL mode.
3. Do not carry out additional charging.
   When additional charging is carried out if refrigerant leaks, the refrigerant composition changes in the refrigeration cycle, that is characteristics of the air conditioner changes, refrigerant exceeding the specified amount is charged, and working pressure in the refrigeration cycle becomes abnormally high pressure, and may cause a rupture or personal injury.




**Fig. 3-4-1 Configuration of refrigerant charging**



Downloaded from AC-Manual.com Manuals

1. Be sure to make setting so that **liquid** can be charged.
2. When using a cylinder equipped with a siphon, liquid can be charged without turning it upside down.

It is necessary for charging refrigerant under condition of liquid because R410A is mixed type of refrigerant. Accordingly, when charging refrigerant from the refrigerant cylinder to the equipment, charge it turning the cylinder upside down if cylinder is not equipped with siphon.




R410A refrigerant is HFC mixed refrigerant. Therefore, if it is charged with gas, the composition of the charged refrigerant changes and the characteristics of the equipment varies.

**Fig. 3-4-2**

## 3-5. Brazing of Pipes

### 3-5-1. Materials for Brazing

**1. Silver brazing filler**

Silver brazing filler is an alloy mainly composed of silver and copper. It is used to join iron, copper or copper alloy, and is relatively expensive though it excels in solderability.

**2. Phosphor bronze brazing filler**

Phosphor bronze brazing filler is generally used to join copper or copper alloy.

**3. Low temperature brazing filler**

Low temperature brazing filler is generally called solder, and is an alloy of tin and lead. Since it is weak in adhesive strength, do not use it for refrigerant pipes.

1. Phosphor bronze brazing filler tends to react with sulfur and produce a fragile compound water solution, which may cause a gas leakage. Therefore, use any other type of brazing filler at a hot spring resort, etc., and coat the surface with a paint.
2. When performing brazing again at time of servicing, use the same type of brazing filler.

### 3-5-2. Flux

**1. Reason why flux is necessary**

- By removing the oxide film and any foreign matter on the metal surface, it assists the flow of brazing filler.
- In the brazing process, it prevents the metal surface from being oxidized.
- By reducing the brazing filler's surface tension, the brazing filler adheres better to the treated metal.



Downloaded from AC-Manual.com Manuals

### 2. Characteristics required for flux

- Activated temperature of flux coincides with the brazing temperature.
- Due to a wide effective temperature range, flux is hard to carbonize.
- It is easy to remove slag after brazing.
- The corrosive action to the treated metal and brazing filler is minimum.
- It excels in coating performance and is harmless to the human body.

As the flux works in a complicated manner as described above, it is necessary to select an adequate type of flux according to the type and shape of treated metal, type of brazing filler and brazing method, etc.

### 3. Types of flux

- **Noncorrosive flux**

  Generally, it is a compound of borax and boric acid.
  It is effective in case where the brazing temperature is higher than 800°C.

- **Activated flux**

  Most of fluxes generally used for silver brazing are this type.
  It features an increased oxide film removing capability due to the addition of compounds such as potassium fluoride, potassium chloride and sodium fluoride to the borax-boric acid compound.

### 4. Piping materials for brazing and used brazing filler/flux

| Piping material | Used brazing filler | Used flux |
|---|---|---|
| Copper - Copper | Phosphor copper | Do not use |
| Copper - Iron | Silver | Paste flux |
| Iron - Iron | Silver | Vapor flux |

1. Do not enter flux into the refrigeration cycle.
2. When chlorine contained in the flux remains within the pipe, the lubricating oil deteriorates. Therefore, use a flux which does not contain chlorine.
3. When adding water to the flux, use water which does not contain chlorine (e.g. distilled water or ion-exchange water).
4. Remove the flux after brazing.

## 3-5-3. Brazing

As brazing work requires sophisticated techniques, experiences based upon a theoretical knowledge, it must be performed by a person qualified.

In order to prevent the oxide film from occurring in the pipe interior during brazing, it is effective to proceed with brazing while letting dry Nitrogen gas (N2) flow.

**Never use gas other than Nitrogen gas.**

### 1. Brazing method to prevent oxidation

1) Attach a reducing valve and a flow-meter to the Nitrogen gas cylinder.
2) Use a copper pipe to direct the piping material, and attach a flow-meter to the cylinder.
3) Apply a seal onto the clearance between the piping material and inserted copper pipe for Nitrogen in order to prevent backflow of the Nitrogen gas.
4) When the Nitrogen gas is flowing, be sure to keep the piping end open.
5) Adjust the flow rate of Nitrogen gas so that it is lower than 0.05 $m^3$/Hr or 0.02 MPa (0.2kgf/$cm^2$) by means of the reducing valve.
6) After performing the steps above, keep the Nitrogen gas flowing until the pipe cools down to a certain extent (temperature at which pipes are touchable with hands).
7) Remove the flux completely after brazing.




**Fig. 3-5-1 Prevention of oxidation during brazing**



Downloaded from AC-Manual.com Manuals

# 4. CONSTRUCTION VIEWS

## 4-1. Indoor Unit




Downloaded from AC-Manual.com Manuals

## 4-2. Outdoor Unit




Downloaded from AC-Manual.com Manuals

# 5. WIRING DIAGRAM

## 5-1. Indoor Unit




Quick check for diagnosing faults

| Check Items | Diagnosis result |
|---|---|
| 1 OPERATION indicator | Check to see if the OPERATION indicator goes on & off when the main switch or circuit breakers turned on, or power cord is plugged in the wall outlet. |
| 2 Terminal block | Check for the voltage between ① and ② is 220 to 240VAC.<br>Check for the voltage between ② and ③ is 15 to 60VDC. |
| 3 Fuse 3.15A | Check Varistor if the fuse is open. |
| 4 DC5V | Check for the voltage between ③ and ④ terminal of CN21. |

Downloaded from AC-Manual.com Manuals

## 5-2. Outdoor Unit




Downloaded from AC-Manual.com Manuals

# 6. SPECIFICATION OF ELECTRICAL PARTS

## 6-1. Indoor Unit

| No. | Parts name | Type | Specifications |
|---|---|---|---|
| 1 | Fan motor | AFS-220-20-4AR | AC Motor with 145°C thermo fuse<br>DC Motor Over Heat protection circuit |
| 2 | Thermo. sensor (TA-sensor) | | 10 kΩ at 25°C |
| 3 | Micro power module (T101) | μRM1260V | |
| 4 | Micro controller unit (IC81) | μPD780076GK-703-9ET-A | |
| 5 | Heat exchanger sensor (TC-sensor) | | 10 kΩ at 25°C |
| 6 | Line filter (L01) | SS11V-R06270 | 27 mH, AC 0.6A |
| 7 | Diode (D01,D02,D03 and D04) | S5688J | |
| 8 | Capacitor (C03) | EKMH401VSN470MP20S | 47μF, 400 V |
| 9 | Fuse (F01) | FJL 250 V 3.15A | 3.15A, 250 V |
| 10 | Regulator IC (IC12) | S7805PIC | 5VDC, 0.5A |
| 11 | Varistor (R21) | TNR10V471K-T8 | 470V |
| 12 | Louver motor | 24BYJ48 | DC 12V |

## 6-2. Outdoor Unit (38NYV025M, 38NYV025M-A)

| No. | Parts name | | Model name | Rating |
|---|---|---|---|---|
| 1 | SC coil | L01 | GET-04051 | 0.6mH, 15A |
| | (Noise filter) | L03 | GET-04052 | 2.0mH,10A |
| 2 | DC-DC transformer | | SWT-72 | Primary side DC280V, Secondary side 7.0 V x 1, 12 V x 1, 17V x 2 |
| 3 | Reactor | | CH-57-Z-T | L=19mH, 10A |
| 4 | Outside fan motor | | SKF-240-20B-1 | 20W |
| 5 | Fan control relay | | G5NB-1A | Coil DC12V Contact AC250V-1.5A |
| 6 | Outside air temp. sensor (TO sensor) | | (Inverter attached) | 10kΩ (25°C) |
| 7 | Heat exchanger temp. sensor (TE sensor) | | (Inverter attached) | 10kΩ (25°C) |
| 8 | Dischenge temp. sensor (TD sensor) | | (Inverter attached) | 62kΩ (20°C) |
| 9 | Terminal block (6P) | | JX0-6B | 20A, AC250V |
| 10 | Fuse | | For protection of switching power source | 3.15A, AC250V |
| | | | For protection of inverter input overcurrent | 25A, AC250V |
| 11 | Electrolytic capacitor | | LLQ2G501KHUBTF | 500μF, DC 400 V x 3 pieces |
| 12 | IGBT | | GT15J321 | 15A, 600 |
| 13 | Compressor | | DA89X1C-23FZ | 3-phases 4-poles 750W |
| 14 | Compressor thermo. | | PW-2AL | OFF: 125 ± 4°C, ON: 90 ± 5°C |
| 15 | Rectifier | | D15XB60-4001 | 15A, 600V |
| 16 | 4-way valve coil | | — | AC220-240V |
| 17 | Running capacitor (for fan motor) | | DS451155NPQB | AC450V, 1.5μF |

Downloaded from AC-Manual.com Manuals

# 7. REFRIGERANT CYCLE DIAGRAM

## 7-1. Refrigerant Cycle Diagram

**42NQV025M / 38NYV025M**
**42NQV025M-A / 38NYV025M-A**




**NOTE :**

- The maximum pipe length of this air conditioner is 10 m. The addition charging of refrigevant is unnecessary because this air condition is design with charge-less specitication.



Downloaded from AC-Manual.com Manuals

## 7-2. Operation Data

**<Cooling>**

| Tempeature condition(°C) | | Model name | Standard pressure | Heat exchanger pipe temp. | | Indoor fan mode | Outdoor fan mode | Compressor revolution |
|---|---|---|---|---|---|---|---|---|
| Indoor | Outdoor | | P (MPa) | T1 (°C) | T2 (°C) | | | (rps) |
| 27/19 | 35/- | 42NQV025M | 0.9 to 1.1 | 9 to 11 | 47 to 49 | High | High | 54 |
| | | 42NQV025M-A | 0.9 to 1.1 | 9 to 11 | 47 to 49 | High | High | 54 |

**<Heating>**

| Tempeature condition(°C) | | Model name | Standard pressure | Heat exchanger pipe temp. | | Indoor fan mode | Outdoor fan mode | Compressor revolution |
|---|---|---|---|---|---|---|---|---|
| Indoor | Outdoor | | P (MPa) | T1 (°C) | T2 (°C) | | | (rps) |
| 20/- | 7/6 | 42NQV025M | 2.4 to 2.6 | 43 to 45 | 0 to 3 | High | High | 68 |
| | | 42NQV025M-A | 2.4 to 2.6 | 43 to 45 | 0 to 3 | High | High | 68 |

**NOTES :**

1. Measure surface temperature of heat exchanger pipe around center of heat exchanger path U bent. (Thermistor themometer)
2. Connecting piping condition : 5 m



Downloaded from AC-Manual.com Manuals

# 8. CONTROL BLOCK DIAGRAM

## 8-1. Indoor Unit




**REMOTE CONTROL**




Downloaded from AC-Manual.com Manuals

## 8-2. Outdoor Unit (38NYV025M, 38NYV025M-A)




Downloaded from AC-Manual.com Manuals

# 9. OPERATION DESCRIPTION

## 9-1. Outline of Air Conditioner Control

This air conditioner is a capacity-variable type air conditioner, which uses AC motor both the indoor fan motor and the outdoor fan motor. And the capacity-proportional control compressor which can change the motor speed in the range from 22 to 83 rps is mounted. The AC motor drive circuit is mounted to the indoor unit. The compressor and the inverter is mounted to the outdoor unit.

The entire air conditioner is mainly controlled by the indoor unit controller.

The indoor unit controller drives the indoor fan motor based upon command sent from the remote controller, and transfers the operation command to the outdoor unit controller.

The outdoor unit controller receives operation command from the indoor unit side, and controls the outdoor fan motor. Besides detecting revolution position of the compressor motor, the outdoor unit controller controls speed of the compressor motor by controlling output voltage of the inverter and switching timing of the supply power (current transfer timing) so that motors drive according to the operation command.

And then, the outdoor unit controller transfers reversely the operating status information of the outdoor unit to control the indoor unit controller.

**As the compressor adopts four-pole brushless DC motor , the frequency of the supply power from in verter to compressor is two-times cycles of the actual number of revolution.**

### 1. Role of indoor unit controller

The indoor unit controller judges the operation commands from the remote controller and assumes the following functions.

- Judgment of suction air temperature of the indoor heat exchanger by using the indoor temp. sensor. (TA sensor)
- Judgment of the indoor heat exchanger temperature by using heat exchanger sensor (TC sensor) (Prevent-freezing control, etc.)
- Louver motor control
- Indoor fan motor operation control
- LED (Light Emitting Diode) display control
- Transferring of operation command signal (Serial signal) to the outdoor unit
- Reception of information of operation status (Serial signal including outside temp. data) to the outdoor unit and judgment/display of error

### 2. Role of outdoor unit controller

Receiving the operation command signal (Serial signal) from the indoor unit controller, the outdoor unit performs its role.

- Compressor operation control
- 4-way valve control

} Operations followed to judgment of serial signal from indoor side

- Detection of inverter input current and current release operation
- Over-current detection and prevention operation to IGBT module (Compressor stop function)
- Compressor and outdoor fan stop function when serial signal is off (when the serial signal does not reach the board assembly of outdoor control by trouble of the signal system)
- Transferring of operation information (Serial signal) from outdoor unit controller to indoor unit controller
- Detection of outdoor temperature and operation revolution control
- Defrost control in heating operation (Temp. measurement by outdoor heat exchanger and control for 4-way valve and outdoor fan)

### 3. Contents of operation command signal (Serial signal) from indoor unit controller to outdoor unit controller

The following three types of signals are sent from the indoor unit controller.

- Operation mode set on the remote controller
- Compressor revolution command signal defined by indoor temperature and set temperature (Correction along with variation of room temperature and correction of indoor heat exchanger temperature are added.)
- Temperature of indoor heat exchanger
- For these signals ([Operation mode] and [Compressor revolution] indoor heat exchanger temperature), the outdoor unit controller monitors the input current to the inverter, and performs the followed operation within the range that current does not exceed the allowable value.

### 4. Contents of operation command signal (Serial signal) from outdoor unit controller to indoor unit controller

The following signals are sent from the outdoor unit controller.

- The current operation mode
- The current compressor revolution
- Outdoor temperature
- Existence of protective circuit operation

For transferring of these signals, the indoor unit controller monitors the contents of signals, and judges existence of trouble occurrence.

Contents of judgment are described below.

- Whether distinction of the current operation status meets to the operation command signal
- Whether protective circuit operates

When no signal is received from the outdoor unit controller, it is assumed as a trouble.



Downloaded from AC-Manual.com Manuals

## 9-2. Operation Description


1. Basic operation ..... 26
   1. Operation control ..... 26
   2. Cooling/Heating operation ..... 27
   3. AUTO operation ..... 27
   4. DRY operation ..... 27
2. Indoor fan motor control ..... 28
3. Capacity control ..... 30
4. Current release control ..... 30
5. Release protective control by temperature of indoor heat exchanger ..... 31
6. Defrost control (Only in heating operation) ..... 32
7. Louver control ..... 33
   1) Louver position ..... 33
   2) Air direction adjustment ..... 33
   3) Swing ..... 33
8. ECO operation ..... 34
9. Temporary operation ..... 35
10. Discharge temperature control ..... 35
11. Remote-A or B selection ..... 36
12. Hi-POWER Mode ..... 37

**9-3. Auto Restart Function** ..... 38

9-3-1. How to Set the Auto Restart Function ..... 38

9-3-2. How to Cancel the Auto Restart Function ..... 39

9-3-3. Power Failure During Timer Operation ..... 39

**9-4. Remote Control** ..... 40

9-4-1. Remote control and its functions ..... 40

9-4-2. Operation of remote control ..... 40

9-4-3. Name and Functions of Indications on Remote Controller ..... 43




Downloaded from AC-Manual.com Manuals

## 9-2. Operation Description

| Item | Operation flow and applicable data, etc. | Description |
|---|---|---|
| 1. Basic operation | 1. Operation control | |

Receiving the user's operation condition setup, the operation statuses of indoor/outdoor units are controlled.

1) The operation conditions are selected by the remote controller as shown in the below.
2) A signal is sent by ON button of the remote controller.
3) The signal is received by a sensor of the indoor unit and processed by the indoor controllers as shown in the below.
4) The indoor controller controls the indoor fan motor and louver motor.
5) The indoor controller sends the operation command to the outdoor controller, and sends/receives the control status with a serial signal.
6) The outdoor controller controls the operation as shown in the left, and also controls the compressor, outdoor fan motor and 4-way valve.






Downloaded from AC-Manual.com Manuals

| Item | Operation flow and applicable data, etc. | Description |
|---|---|---|
| **1. Basic operation** | **2. Cooling/Heating operation**<br>The operations are performed in the following parts by controls according to cooling/heating conditions.<br>1) Receiving the operation ON signal of the remote controller, the cooling or heating operation signal starts being transferred form the indoor controller to the outdoor unit.<br>2) At the indoor unit side, the indoor fan is operated according to the contents of "**2. Indoor fan motor control**" and the louver according to the contents of "**9. Louver control**", respectively.<br>3) The outdoor unit controls the outdoor fan motor, compressor and 4-way valve according to the operation signal sent from the indoor unit.<br>  | |
| | **3. AUTO operation**<br>Selection of operation mode<br>As shown in the following figure, the operation starts by selecting automatically the status of room temperature (Ta) when starting AUTO operation.<br>*1. When reselecting the operation mode, the fan speed is controlled by the previous operation mode.<br>  | 1) Detects the room temperature (Ta) when the operation started.<br>2) Selects an operation mode from Ta in the left figure.<br>3) Fan operation continues until an operation mode is selected.<br>4) When AUTO operation has started within 2 hours after heating operation stopped and if the room temperature is 20°C or more, the fan operation is performed with "Super Ultra LOW" mode for 3 minutes.<br>Then, select an operation mode.<br>5) If the status of compressor-OFF continues for 15 minutes the room temperature after selecting an operation mode (COOL/HEAT), reselect an operation mode. |
| | **4. DRY operation**<br>DRY operation is performed according to the difference between room temperature and the setup temperature as shown below.<br>In DRY operation, fan speed is controlled in order to prevent lowering of the room temperature and to avoid air flow from blowing directly to persons.<br>  | 1) Detects the room temperature (Ta) when the DRY operation started.<br>2) Starts operation under conditions in the left figure according to the temperature difference between the room temperature and the setup temperature (Tsc).<br>Setup temperature (Tsc)<br>= Set temperature on remote controller (Ts) + (0.0 to 1.0)<br>3) When the room temperature is lower 1°C or less than the setup temperature, turn off the compressor. |



Downloaded from AC-Manual.com Manuals

| Item | Operation flow and applicable data, etc. | Description |
|---|---|---|
| **2. Indoor fan motor control** | **<In cooling operation>**<br>(This operation controls the fan speed at indoor unit side.)<br>The indoor fan (cross flow fan) is operated by the phase-control induction motor. The fan rotates in 5 stages in MANUAL mode, and in 5 stages in AUTO mode, respectively. (Table 1) | |




**(Fig. 1)**

| Indication | Fan speed |
|---|---|
| L | W6 |
| L+ | (L + M) / 2 |
| M | W9 |
| M+ | (M + H) / 2 |
| H | WC |

**(Fig. 2)**




**(Table 1) Indoor fan and air flow rate**

| Fan speed level | COOL | HEAT | DRY | 42NQV025M 42NQV025M-A | |
|---|---|---|---|---|---|
| | | | | Fan speed (rpm) | Air flow rate ($m^3/h$) |
| WF | | UH | | 1350 | 607 |
| WE | | H | | 1300 | 576 |
| WD | UH | M+ | UH | 1250 | 554 |
| WC | H | | H | 1200 | 522 |
| WB | M+ | M | M+ | 1120 | 486 |
| WA | | | M | 1100 | 468 |
| W9 | M | L+ | | 1040 | 444 |
| W8 | | L | | 960 | 402 |
| W7 | L+ | L- | L+ | 910 | 376 |
| W6 | L | | L | 880 | 360 |
| W5 | L- | UL | L- | 830 | 334 |
| W4 | UL | | UL | 800 | 318 |
| W3 | SUL | | SUL | 700 | 266 |
| W2 | | SUL | | 650 | 239 |
| W1 | | | | 600 | 213 |

*** Symbols**

| | |
|---|---|
| UH | : Ultra High |
| H | : High |
| M+ | : Medium+ |
| M | : Medium |
| L+ | : Low+ |
| L | : Low |
| L- | : Low– |
| UL | : Ultra Low |
| SUL | : Super Ultra Low |

* The fan speed broadly varies due to position of the louver, etc. The described value indicates one under condition of inclining downward blowing.

1) When setting the fan speed to L, L+, M, M+ or H on the remote controller, the operation is performed with the constant speed shown in Fig. 1.
2) When setting the fan speed to AUTO on the remote controller, revolution of the fan motor is controlled to the fan speed level shown in Fig. 2 and Table 1 according to the setup temperature, room temperature, and heat exchanger temperature.



Downloaded from AC-Manual.com Manuals

| Item | Operation flow and applicable data, etc. | Description |
|---|---|---|
| **2. Indoor fan motor control** | **<In heating operation>** | 1) When setting the fan speed to L, L+, M, M+ or H on the remote controller, the operation is performed with the constant speed shown in Fig. 3 and Table 1.<br>2) When setting the fan speed to AUTO on the remote controller, revolution of the fan motor is controlled to the fan speed level shown in Fig. 5 according to the set temperature and room temperature.<br>3) Min air flow rate is controlled by temperature of the indoor heat exchanger (Tc) as shown in Fig. 4.<br>4) Cold draft prevention, the fan speed is controlled by temperature of the indoor heat exchanger (Tc) as shown in Fig. 6.<br>5) In order to prevent Cold draft when compressor step during heating operation. Then louver will move to upper position and fan speed will reduce or off. |




| Indication | Fan speed |
|---|---|
| L | W8 |
| L+ | (L + M) / 2 |
| M | WA |
| M+ | (M + H) / 2 |
| H | WE |

**(Fig. 3)**

**(Fig. 4)**




**(Fig. 5)**

**Cold draft preventive control**




**(Fig. 6)**

**[In starting and in stability]**

| | In starting | In stability |
|---|---|---|
| FAN AUTO | • Until 12 minutes passed after operation start<br>• When 12 to 25 minutes passed after operation start and room temp. is 3°C or lower than set temp. | • When 12 to 25 minutes passed after operation start and room temp. is higher than (set temp. –3°C)<br>• When 25 minutes or more passed after operation start |
| FAN Manual | • Room temp. < Set temp. –4°C | • Room temp. ≥ Set temp. –3.5°C |



Downloaded from AC-Manual.com Manuals

| Item | Operation flow and applicable data, etc. | Description |
|---|---|---|
| **3. Capacity control** | The cooling or heating capacity depending on the load is adjusted.<br>According to difference between the setup value of temperature and the room temperature, the capacity is adjusted by the compressor revolution. | 1) The difference between set temperature on remote controller (Ts) and room temperature (Ta) is calculated.<br>2) According to the temperature difference, the correction value of Hz signal which determines the compressor speed is set up.<br>3) The rotating position and speed of the motor are detected by the electromotive force occurred on the motor winding with operation of the compressor.<br>4) According to the difference resulted from comparison of the correction value of Hz signal with the present operation Hz, the inverter output and the commutation timing are varied.<br>5) Change the compressor motor speed by outputting power to the compressor.<br>* The contents of control operation are same in cooling operation and heating operation |
| **4. Current release control** | This function prevents troubles on the electronic parts of the compressor driving inverter.<br>This function also controls drive circuit of the compressor speed so that electric power of the compressor drive circuit does not exceed the specified value. | 1) The input current of the outdoor unit is detected in the inverter section of the outdoor unit.<br>2) According to the detected outdoor temperature, the specified value of the current is selected.<br>3) Whether the current value exceeds the specified value or not is judged.<br>4) If the current value exceeds the specified value, this function reduces the compressor speed and controls speed up to the closest one commanded from the indoor unit within the range which does not exceed the specified value. |


Remote controller
Indoor unit
Set temp. (Ts)
Room temp. (Ta)
Ts –Ta
Correction of Hz signal
Detection of electromotive force of compressor motor winding
Detection of motor speed and rotor position
Correction value of Hz signal ≤ Operating Hz
Inverter output change
Commutation timing change
Change of compressor speed




| Outdoor temp. | Cooling current release value | Heating current release value |
|---|---|---|
| | 42NQV025M<br>42NQV025M-A | 42NQV025M<br>42NQV025M-A |
| 45°C | 3.60A | 7.72A |
| 40°C | 5.17A | |
| 44°C | | |
| 16°C | 5.17A | |
| 39°C | | |
| 11°C | | |
| 15.5°C | | |
| 10.5°C | | 9.26A |
| | | 10.80A |



Downloaded from AC-Manual.com Manuals

| Item | Operation flow and applicable data, etc. | Description |
|---|---|---|
| **5. Release protective control by temperature of indoor heat exchanger** | **<In cooling/dry operation>**<br>(Prevent-freezing control for indoor heat exchanger)<br>In cooling/dry operation, the sensor of indoor heat exchanger detects evaporation temperature and controls the compressor speed so that temperature of the heat exchanger does not exceed the specified value.<br>  <br> | 1) When temperature of the indoor heat exchanger drops below 5°C, the compressor speed is reduced. (P zone)<br>2) When temperature of the indoor heat exchanger rises in the range from 6°C to under 7°C, the compressor speed is kept. (Q zone)<br>3) When temperature of the indoor heat exchanger rises to 7°C or higher, the capacity control operation returns to the usual control in cooling operation. (R zone) |
| | **<In heating operation>**<br>(Prevent-overpressure control for refrigerating cycle)<br>In heating operation, the sensor of indoor heat exchanger detects condensation temperature and controls the compressor speed so that temperature of the heat exchanger does not exceed the specified value.<br>  <br> | 1) When temperature of the indoor heat exchanger rises in the range from 50°C to 55°C, the compressor speed is kept. (Q zone)<br>When temperature of the indoor heat exchanger drops in the range from 46°C to under 55°C, the compressor speed is kept. (Q zone)<br>2) When temperature of the indoor heat exchanger rises to 55°C or higher, the compressor speed is reduced. (P zone)<br>3) When temperature of the indoor heat exchanger does not rise to 50°C, or when it drops below to 46°C, the capacity control operation returns to the usual control in heating operation. (R zone) |



Downloaded from AC-Manual.com Manuals

| Item | Operation flow and applicable data, etc. | Description |
|---|---|---|
| **6. Defrost control (Only in heating operation)** | (This function removes frost adhered to the outdoor heat exchanger.)<br>The temperature sensor of the outdoor heat exchanger (Te sensor) judges the frosting status of the outdoor heat exchanger and the defrost operation is performed with 4-way valve reverse defrost system. | The necessity of defrost operation is detected by the outdoor heat exchanger temperature. The conditions to detect the necessity of defrost operation differ in A, B, or C zone each. (Table 1)<br>**<Defrost operation>**<br>• Defrost operation in A to C zones<br>1) Stop operation of the compressor for 20 seconds.<br>2) Invert (OFF) 4-way valve 10 seconds after stop of the compressor.<br>3) The outdoor fan stops at the same time when the compressor stops.<br>4) When temperature of the indoor heat exchanger becomes 38°C or lower, stop the indoor fan.<br>**<Finish of defrost operation>**<br>• Returning conditions from defrost operation to heating operation<br>1) Temperature of outdoor heat exchanger rises to +8°C or higher.<br>2) Temperature of outdoor heat exchanger is kept at +5°C or higher for 80 seconds.<br>3) Defrost operation continues for 15 minutes.<br>**<Returning from defrost operation>**<br>1) Stop operation of the compressor for approx. 50 seconds.<br>2) Invert (ON) 4-way valve approx. 40 seconds after stop of the compressor.<br>3) The outdoor fan starts rotating at the same time when the compressor starts. |




* The minimum value of Te sensor 10 to 15 minutes after start of operation is stored in memory as Te0.

**Table 1**

| | |
|---|---|
| **A zone** | When Te0 - TE ≥ 2.5 continued for 2 minutes in A zone, defrost operation starts. |
| **B zone** | When the operation continued for 2 minutes in B zone, defrost operation starts. |
| **C zone** | When Te0 - TE ≥ 3 continued for 2 minutes in C zone, defrost operation starts. |



Downloaded from AC-Manual.com Manuals

| Item | Operation flow and applicable data, etc. | Description |
|---|---|---|
| **7. Louver control**<br>1) Louver position | This function controls the air direction of the indoor unit.<br>• The position is automatically controlled according to the operation mode (COOL/HEAT).<br>• The set louver position is stored in memory by the microcomputer, and the louver returns to the stored position when the next operation is performed. (Cooling/Heating memory position)<br>The angle of the louver is indicated as the louver closes fully is 0°.<br><br>1) Louver position in cooling operation<br>  <br>Initial setting of "Cooling storage position"<br>Louver : Directs downward (48°)<br><br>**2) Louver position in heating operation**<br>  <br>**Heating operation/ AUTO (HEAT)**<br>Initial setting of "Heating storage position"<br>Louver : Directs downward (115.7°) | |
| 2) Air direction adjustment |  <br>**Air direction**<br>Horizontal blowing / Inclined blowing / Blowing downward / Inclined blowing / Horizontal blowing | • The louver position can be arbitrarily set up by pressing [FIX] button. |
| 3) Swing | • Swing operation is performed in width 35° with the stop position as the center.<br>• If the stop position exceeds either upper or lower limit position, swing operation is performed in width 35° from the limit which the stop position exceeded. | • Swing<br>When pressing [SWING] button during operation, the louver starts swinging. |



Downloaded from AC-Manual.com Manuals

| Item | Operation flow and applicable data, etc. | Description |
|---|---|---|
| **8. ECO operation** | When pressing [ECO] button on the remote controller, a Economic operation is performed.<br>**<Cooling operation>**<br>This function operates the air conditioner with the difference between the set and the room temperature as shown in the following figure. | **<Cooling operation>**<br>1) The control target temperature increase 0.5ºC per hour up to 2ºC starting from the set temperature when ECONO has been received.<br>2) The indoor fan speed is depend on presetting and can change every speed after setting ECO operation.<br>3) The compressor speed is controlled as shown in the left figure. |




* 12 (DRY max - COOL min) /6 x 5 + COOL min
* 11 (DRY max - COOL min) /6 x 4 + COOL min
* 10 (DRY max - COOL min) /6 x 3 + COOL min
* 9 (DRY max - COOL min) /6 x 2 + COOL min
* 8 (DRY max - COOL min) /6 x 1 + COOL min

| Hz | 42NQV025M, 42NQV025M-A |
|---|---|
| Cool min | 22 |
| Dry max | 32 |

**<Heating operation>**

**<Heating operation>**

1) Setting the compressor speed to Max. aHz, the temperature zone in which the operation can be performed with Max. cHz is gradually widened after 30 minutes passed when starting ECO operation.
2) The indoor fan speed is depend on presetting and can change every speed after setting ECO operation.




| Hz | 42NQV025M<br>42NQV025M-A |
|---|---|
| a | 22 |
| c | 52 |



Downloaded from AC-Manual.com Manuals

| Item | Operation flow and applicable data, etc. | Description |
|---|---|---|
| **9. Temporary operation** | Pressing [RESET] button starts the temporary operation of [AUTO] operation. When keeping [RESET] button pressed for 10 seconds or more, the temporary [COOL] operation is performed.<br>  | 1) When pressing [RESET] button, the temporary [AUTO] operation starts.<br>2) When keeping [RESET] button pressed for 3 seconds or more, Pi, Pi, Pi sound is heard and [AUTO RESTART] control is changed.<br>3) When keeping [RESET] button pressed for 10 seconds or more, “Pi” sound is heard and the temporary [COOL] operation starts.<br>4) If the filter lamp goes on, press [RESET] button to go off the filter lamp, and then press [RESET] button again.<br>5) To stop the temporary operation, press the button again. |
| **10. Discharge temperature control**<br><br>**Td value** / **Control operation**<br>117°C: Judges as an error and stops the compressor.<br>112°C: Reduce the compressor speed.<br>108°C: Reduce slowly compressor speed.<br>105°C: Keeps the compressor speed.<br>98°C: If the operation is performed with lower speed than one commanded by the serial signal, speed is slowly raised up to the commanded speed.<br>Operates with speed commanded by the serial signal. | | **1. Purpose**<br>This function detects error on the refrigerating cycle or error on the compressor, and performs protective control.<br>**2. Operation**<br>• Control of the compressor speed<br>The speed control is performed as described in the left table based upon the discharge temperature. |



Downloaded from AC-Manual.com Manuals

| Item | Operation flow and applicable data, etc. | Description |
|---|---|---|
| **11. Romote-A or B selection** | **Setting the remote controller**<br>To separate using of remote control for each indoor unit in case of 2 air conditioner are installed nearly.<br>**Remote Control B Setup.**<br>1) Press RESET button on the indoor unit to turn the air conditioner ON.<br>2) Point the remote control at the indoor unit.<br>3) Push and hold CHK • button on the Remote Control by thetip of the pencil. "00" will be shown shown on the display.<br>4) Press MODE • during pushing CHK •. "B" will show on the display and "00" will disappear and the air conditioner will turn OFF. The Remote Control B is memorized.<br><br>Note : 1. Repeat above step to reset Remote Control to be A.<br>2. Remote Control A has mot "A" display.<br>3. Default setting of Remote Control from factory is A.<br><br>  <br> | **1. Purpose**<br>This operation is to operate only one indoor unit using one remote controller.<br>**2. Description**<br>When operating one indoor unit in a situation where two indoor units have been installed in the same room or nearby rooms, this operation prevents the remote controller signal from being received simultaneously by both units, thus preventing both units from operating.<br>**3. Operation**<br>The indoor unit on which the remote controller selection has been set to B receives the signal of the remote controller also set to B.<br>(At the factory the remote controller selection is set to A on all the indoor units. There is no A setting display.) |



Downloaded from AC-Manual.com Manuals

| Item | Operation flow and applicable data, etc. | Description |
|---|---|---|
| **12. Hi-POWER Mode** | **([Hi-POWER] button on the remote controller is pressed)**<br>When [Hi-POWER] button is pressed while the indoor unit is in Auto, Cooling or Heating operation, Hi-POWER mark is indicated on the display of the remote controller and the unit operates as follows.<br>**1. Automatic operation**<br>• The indoor unit operates in according to the current operation.<br>**2. Cooling operation**<br>• The preset temperature drops 1ºC (The value of the preset temperature on the remote controller does not change.) The indoor unit's fan speed level increase 1 tap<br>**3. Heating operation**<br>• The preset temperature increases 2ºC (The value of the preset temperature on the remote controller does not change.) The indoor unit's fan speed level increase 1 tap<br>**4. The Hi-POWER mode can not be set in Dry operation** | |



Downloaded from AC-Manual.com Manuals

## 9-3. Auto Restart Function

This indoor unit is equipped with an automatic restarting function which allows the unit to restart operating with the set operating conditions in the event of a power supply being accidentally shut down.
The operation will resume without warning three minutes after power is restored.

This function is not set to work when shipped from the factory. Therefore it is necessary to set it to work.

### 9-3-1. How to Set the Auto Restart Function

To set the auto restart function, proceed as follows:

The power supply to the unit must be on ; the function will not set if the power is off.

Press the [RESET] button located in the center of the front panel continuously for three seconds.

The unit receives the signal and beeps three times.

The unit then restarts operating automatically in the event of power supply being accidentally shut down.

- **When the unit is standby (Not operating)**

| Operation | Motions |
|---|---|
| Press [RESET] button for more than three seconds. (Less than 10 seconds)<br>  <br>RESET button | The unit is on standby.<br>↓<br>The unit starts to operate. The green indicator is on.<br>↓ After approx. three seconds,<br>The unit beeps three times and continues to operate. **The green indicator flashes for 5 seconds.**<br>If the unit is not required to operate at this time, press [RESET] button once more or use the remote controller to turn it off. |

- **When the unit is in operation**

| Operation | Motions |
|---|---|
| Press [RESET] button for more than three seconds. (Less than 10 seconds)<br>  <br>RESET button | The unit is in operation. The green indicator is on.<br>↓<br>The unit stops operating. The green indicator is turned off.<br>↓ After approx. three seconds,<br>The unit beeps three times. **The green indicator flashes for 5 seconds.**<br>If the unit is required to operate at this time, press [RESET] button once more or use the remote controller to turn it on. |

- While the filter check indicator is on, the RESET button has the function of filter reset betton.



Downloaded from AC-Manual.com Manuals

### 9-3-2. How to Cancel the Auto Restart Function

To cancel auto restart function, proceed as follows :

Repeat the setting procedure : the unit receives the signal and beeps three times.

The unit will be required to be turned on with the remote controller after the main power supply is turned off.

- **When the system is on stand-by (not operating)**

| Operation | Motions |
|---|---|
| Press [RESET] button for more than three seconds. (Less than 10 seconds)<br>  <br>RESET button | The unit is on standby.<br>↓<br>The unit starts to operate. The green indicator is on.<br>↓ After approx. three seconds,<br>The unit beeps three times and continues to operate.<br>If the unit is not required to operate at this time, press [RESET] button once more or use the remote controller to turn it off. |

- **When the system is operating**

| Operation | Motions |
|---|---|
| Press [RESET] button for more than three seconds. (Less than 10 seconds)<br>  <br>RESET button | The unit is in operation. The green indicator is on.<br>↓<br>The unit stops operating. The green indicator is turned off.<br>↓ After approx. three seconds,<br>The unit beeps three times.<br>If the unit is required to operate at this time, press [RESET] button once more or use the remote controller to turn it on. |

### 9-3-3. Power Failure During Timer Operation

When the unit is turned off because of power failure during timer operation, the timer operation is cancelled. In that case, set the timer operation again.

**NOTE :**

The Everyday Timer is reset while a command signal can be received from the remote controller even if it stopped due to a power failure.



Downloaded from AC-Manual.com Manuals

## 9-4. Remote control

### 9-4-1. Remote control and its functions

① Infrared signal emitter
② Start/Stop button ( )
③ Mode select button ( )
④ Temperature button ( )
⑤ Fan speed button ( )
⑥ Swing louver button ( )
⑦ Set louver button ( )
⑧ On timer button ( )
⑨ Off timer button ( )
⑩ Sleep timer button ( )
⑪ Setup button ( )
⑫ Clear button ( )
⑬ Memory and Preset button ( )
⑭ High power button ( )
⑮ Economy button ( )
⑯ Filter reset button ( )
⑰ Clock reset button ( )
⑱ Check button ( )




**Note:** Some models, remote will have text above the buttons.

---

### 9-4-2. Operation of remote control

**1. AUTOMATIC OPERATION**

To automatically select cooling, heating, or fan only operation.

1. Press M MODE : Select A.
2. Press MODE : Set the desired temperature.

**2. COOLING / HEATING / FAN ONLY OPERATION**

1. Press M MODE : Select Cool, Heat, or Fan only.
2. Press MODE : Set the desired temperature.
   Cooling: Min. 17°C, Heating : Max, 30°C, Fan Only: No temperature indication
3. Press : Select AUTO, LOW, LOW+, MED, MED+, or HIGH.

**3. DRY OPERATION (COOLING ONLY)**

For dehumidification, a moderate cooling performance is controlled automatically.

1. Press M MODE : Select Dry .
2. Press MODE : Set the desired temperature.

**4. Hi-POWER OPERATION**

To automatically control room temperature and airflow for faster cooling or heating operation (except in DRY and FAN ONLY mode)

Press HI-POWER : Start and stop the operation.



Downloaded from AC-Manual.com Manuals

## 5. ECO OPERATION

To automatically control room to save energy (except in DRY and FAN ONLY mode)

Press Ⓔ : Start and stop the operation.

**Note:** Cooling operation; the set temperature will increase automatically 1 degree/ hour for 2 hours (maximum 2 degrees increase). For heating operation the set temperature will decrease.

## 6. TEMPORARY OPERATION

In case of the misplaced or discharged remote control

- Pressing the RESET button, the unit can start or stop without using the remote control.
- Operation mode is set on AUTOMATIC operation, preset temperature is 24°C and fan operation is automatic speed.



## 7. TIMER OPERATION

| | Setting the ON Timer | Setting the OFF Timer |
|---|---|---|
| 1 | Press ON : Set the desired ON timer. | Press OFF : Set the desired OFF timer. |
| 2 | Press : Set the timer | Press : Set the timer. |
| 3 | Press : Cancel the timer | Press : Cancel the timer |

Everyday timer allows the user to set both the ON & OFF timers and will be activated on a daily basis.

**Setting Everyday Timer**

| | | | |
|---|---|---|---|
| 1 | Press ON : Set the ON timer. | 3 | Press . |
| 2 | Press OFF : Set the OFF timer. | 4 | Press button during the (⬆ or ⬇) mark flashing. |

· During the every day timer is activation, both arrows (⬆ or ⬇) are indicated.

**Note:**

· Keep the remote control in accessible transmission to the indoor unit; otherwise, the time lag of up to 15 minutes will occur.

· The setting will be saved for the next same operation.

## 8. PRESET OPERATION

Set your preferred operation for future use. The setting will be memorized by the unit for future operation (except air flow direction).

1. Select your preferred operation.
2. Press and hold Ⓟ for 3 seconds to memorize the setting. The ⓟ mark displays.
3. Press Ⓟ: Operate the preset operation.



Downloaded from AC-Manual.com Manuals

## 9. AUTO RESTART OPERATION

To automatically restart the conditioner after the power failure (Power of the unit must be on.)

**Setting**

1. Press and hold the RESET button on the indoor unit for 3 seconds to set the operation. (3 beep sound and OPERATION lamp blink 5 time/sec for 5 secpmds)
   - Do not operate ON timer and OFF timer.
2. Press and hold the RESET button on the indoor unit for 3 seconds to cancel the operation. (3 beep sound but OPERATION lamp does not blink)

## 10. SLEEP TIMER OPERATION

To start the sleep timer (OFF timer) operation

Press ⏱ : Select 1, 3, 5 or 9 hrs for OFF timer operation.



Downloaded from AC-Manual.com Manuals

### 9-4-3. Name and Functions of Indications on Remote Controller

**[Display]**

All indications, except for the clock time indicator, are displayed by pressing the ⏻ button.

**1** **Transmission mark**

This transmission mark ▲ indicates when the remote controller transmits signals to the indoor unit.

**2** **Mode indicator**

Indicates the current operation mode.
(AUTO : Automatic control, A : Auto changeover control, ☼ : Cool, 💧 : Dry, ☀ : Heat, ✣ : Fan only)

**3** **Temperature indicator**

Indicates the temperature setting.
(17°C to 30°C)

**4** **FAN speed indicator**

Indicates the selected fan speed.

AUTO or five fan speed levels

(LOW ▁ , LOW⁺ ▁▂ , MED ▁▂▃ , MED⁺ ▁▂▃▄ , HIGH ▁▂▃▄▅ ) can be shown.

Indicates AUTO when the operating mode is either AUTO or 💧 : Dry.

**5** **TIMER and clock time indicator**

The time setting for timer operation or the clock time is indicated.

The current time is always indicated except during TIMER operation.

**6** **Hi-POWER indicator**

Indicates when the Hi-POWER operation starts.

Press the Hi-POWER button to start and press it again to stop the operation.

**7** **Ⓟ (PRESET) indicator**

Flashes for 3 seconds when the PRESET button is pressed during operation.

The Ⓟ mark is shown when holding down the button for more than 3 seconds while the mark is flashing.

Press another button to turn off the mark.

**8** **ECO indicator**

Indicates when the ECO is in activated.

Press the ECO button to start and press it again to stop operation.

**9** **A, B change indicator remote controller**

When the remote controller switching function is set,"B" appears in the remote controller display. (When the remote controller setting is "A", there is no indication at this position.)

**10** **Swing**

Indicates when louver is swing.
Press swing button to start the swing operation and press it again to stop the swing operation.






Downloaded from AC-Manual.com Manuals

## 9-5. Hi-POWER Mode

### ([Hi-POWER] button on the remote controller is pressed)

When [Hi-POWER] button is pressed while the indoor unit is in Auto, Cooling or Heating operation, Hi-POWER mark is indicated on the display of the remote controller and the unit operates as follows.

**1. Automatic operation**

- The indoor unit operates in according to the current operation.

**2. Cooling operation**

- The preset temperature drops 1ºC.
  (The value of the preset temperature on the remote controller does not change.)

**3. Heating operation**

- The preset temperature increases 2ºC.
  (The value of the preset temperature on the remote controller does not change.)

**4. The Hi-POWER mode can not be set in Dry operation**



Downloaded from AC-Manual.com Manuals

# 10. INSTALLATION PROCEDURE

## 10-1-1. Installation Diagram of Indoor and Outdoor Units




For the rear left and left piping




Insert the cushion between the indoor unit and wall, and tilt the indoor unit for better operation.

Do not allow the drain hose to get slack.




Make sure to run the drain hose sloped downward.

The auxiliary piping can be connected to the left, rear left, rear right, right, bottom right or bottom left.




Insulate the refrigerant pipes separately with insulation, not together.




Before installing the wireless remote control

- With the remote control cover open, load the batteries supplied correctly, obwerving their polarity.




Downloaded from AC-Manual.com Manuals

### 10-1-2. Optional installation parts

| Part Code | Parts name | Q'ty |
|---|---|---|
| Ⓐ | Refrigerant piping<br>Liquid side : ∅6.35 mm<br>Gas side : ∅9.52 mm | One each |
| Ⓑ | Pipe insulating material<br>(polyethylene foam, 6 mm thick) | 1 |
| Ⓒ | Putty, PVC tapes | One each |

**<Fixing bolt arrangement of outdoor unit>**




**Fig. 10-1-2**

- Secure the outdoor unit with the fixing bolts and nuts if the unit is likely to be exposed to a strong wind.
- Use ∅8 mm or ∅10 mm anchor bolts and nuts.
- If it is necessary to drain the defrost water, attach drain nipple ⑨ to the bottom plate of the outdoor unit before installing it.

Downloaded from AC-Manual.com Manuals

### 10-1-3. Accessory and installation parts

| Part No. | Part name (Q'ty) | Part No. | Part name (Q'ty) | Part No. | Part name (Q'ty) |
|---|---|---|---|---|---|
| ① |  Installation plate x 1 | ④ |  Remote control holder x 1 | ⑦ | Mounting screw ∅4 x 25 ℓ x 6 |
| ② |  Wireless remote control x 1 | ⑤ |  Nano-Silver Ginseng filter x 1 | ⑧ | Pan head wood screw ∅3.1 x 16 ℓ x 2 |
| ③ |  Battery x 2 | ⑥ |  Nano-Photo Copper Zinc filter x 1 | ⑨ |  Drain nipple* x 1 |

**Others**

| Name |
|---|
| Owner's manual |
| Installation manual |

The part marked with asterisk (*) is packaged with the outdoor unit.

Downloaded from AC-Manual.com Manuals

**10-1-4. Installation/Servicing Tools**

**<Changes in the product and components>**

In the case of an air conditioner using R410A, in order to prevent any other refrigerant from being charged accidentally, the service port diameter of the outdoor unit control valve (3 way valve) has been changed. (1/2 UNF 20 threads per inch)

- In order to increase the pressure resisting strength of the refrigerant piping, flare processing diameter and size of opposite side of flare nuts has been changed. (for copper pipes with nominal dimensions 1/2 and 5/8)

**New tools for R410A**

| New tools for R410A | Applicable to R22 model | | Changes |
|---|---|---|---|
| Gauge manifold | × | | As pressure is high, it is impossible to measure by means of conventional gauge. In order to prevent any other refrigerant from being charged, each port diameter has been changed. |
| Charge hose | × | | In order to increase pressure resisting strength, hose materials and port size have been changed (to 1/2 UNF 20 threads per inch).<br>When purchasing a charge hose, be sure to confirm the port size. |
| Electronic balance for refrigerant charging | ○ | | As pressure is hight and gasification speed is fast, it is difficult to read the indicated value by means of charging cylinder, as air bubbles occur. |
| Torque wrench (nominal diam. 1/2, 5/8) | × | | The size of opposite sides of flare nuts have been increased. Incidentally, a common wrench is used for nominal diameters 1/4 and 3/8. |
| Flare tool (clutch type) | ○ | | By increasing the clamp bar's receiving hole, strength of spring in the tool has been improved. |
| Gauge for projection adjustment | — | | Used when flare is made by using conventional flare tool. |
| Vacuum pump adapter | ○ | | Connected to conventional vacuum pump. It is necessary to use an adapter to prevent vacuum pump oil from flowing back to the charge hose.<br>The charge hose connecting part has two ports-one for conventional refrigerant (7/16 UNF 20 threads per inch) and one for R410A. If the vacuum pump oil (mineral) mixes with R410A a sludge may occur and damage the equipment. |
| Gas leakage detector | × | | Exclusive for HFC refrigerant. |

- Incidentally, the "refrigerant cylinder" comes with the refrigerant designation (R410A) and protector coating in the U. S's ARI specified rose color (ARI color code: PMS 507).
- Also, the "charge port and packing for refrigerant cylinder" require 1/2 UNF 20 threads per inch corresponding to the charge hose's port size.

Downloaded from AC-Manual.com Manuals

## 10-2. Indoor Unit

### 10-2-1. Installation place

- A place which provides the spaces around the indoor unit as shown in the above diagram.
- A place where there is no obstacle near the air inlet and outlet.
- A place that allows easy installation of the piping to the outdoor unit.
- A place which allows the front panel to be opened.
- The indoor unit shall be installed as top of the indoor unit comes to at least 2 m height.
  Also it must be avoided to put anything on the top of the indoor unit.

**CAUTION**

- Direct sunlight to the indoor unit's wireless receiver should be avoided.
- The microprocessor in the indoor unit should not be too close to RF noise sources.
  (For details, see the owner's manual.)

**<Remote controller>**

- A place where there are no obstacles such as a curtain that may block the signal from the indoor unit.
- Do not install the remote control in a place exposed to direct sunlight or close to a heating source, such as a stove.
- Keep the remote control at least 1 m apart from the nearest TV set or stereo equipment. (This is necessary to prevent image disturbances or noise interference.)
- The location of the remote control should be determined as shown below.




**Fig. 10-2-1**

### 10-2-2. Cutting a hole and mounting installation plate

**<Cutting a hole>**

When installing the refrigerant pipes from the rear.




The center of the pipe hole is above the arrow.

**Fig. 10-2-2**

1. After determining the pipe hole position on the mounting plate (➡), drill the pipe hole (∅65 mm) at a slight downward slant to the outdoor side.

**NOTE:**

- When drilling a wall that contains a metal lath, wire lath or metal plate, be sure to use a pipe hole brim ring sold separately.

**<Mounting the installation plate>**

For installation of the indoor unit, use the paper pattern on the back.




**Fig. 10-2-3**

Downloaded from AC-Manual.com Manuals

**<When the installation plate is directly mounted on the wall>**

1. Securely fit the installation plate onto the wall by screwing it in the upper and lower parts to hook up the indoor unit.
2. To mount the installation plate on a concrete wall with anchor bolts, utilize the anchor bolt holes as illustrated in the above figure.
3. Install the installation plate horizontally in the wall.

**CAUTION**

When installing the installation plate with a mounting screw, do not use the anchor bolt hole. Otherwise the unit may fall down and result in personal injury and property damage.




**Fig. 10-2-4**




**Fig. 10-2-5**

**CAUTION**

Failure to firmly install the unit may result in personal injury and property damage if the unit falls.

- In case of block, brick, concrete or similar type walls, make 5 mm dia. holes in the wall.
- Insert clip anchors for appropriate mounting screws ⑦.

**NOTE:**

- Secure four corners and lower parts of the installation plate with 4 to 6 mounting screws to install it.

**9-2-3. Electrical work**

1. The supply voltage must be the same as the rated voltage of the air conditioner.
2. Prepare the power source for exclusive use with the air conditioner.

**NOTE:**

- Wire type : More than H07RN-F or 245 IEC66 (1.0 $mm^2$ or more)

**CAUTION**

- This appliance can be connected to the mains in either of the following two ways.
  (1) Connection to fixed wiring :
  A switch or circuit breake which disconnects all poles and has a contact separation of at least 3 mm must be incorporate in the fixed wiring. An approved circuit breaker or switches must used.
  (2) Connection with power supply plug :
  Attach power supply plug with power cord and plug it into wall outlet. An approved power supply cord and plug must be used.

**NOTE:**

- Perform wiring works so as to allow a generous wiring capacity.

Downloaded from AC-Manual.com Manuals

### 10-2-4. Wiring connection

**<How to connect the connecting cable>**

**Wiring of the connecting cable can be carried out without removing of the front panel.**

1. Remove the air inlet grille.
   Open the air inlet grille upward and pull it toward you.
2. Remove the terminal cover and cord clamp.
3. Insert the connecting cable (according to the local cords) into the pipe hole on the wall.
4. Take out the connecting cable through the cable slot on the rear panel so that it protrudes about 15 cm from the front.
5. Insert the connecting cable fully into the terminal block and secure it tightly with screws.
6. Tightening torque : 1.2 N·m (0.12 kgf·m)
7. Secure the connecting cable with the cord clamp.
8. Fix the terminal cover, rear plate bushing and air inlet grille on the indoor unit.

**CAUTION**

- Be sure to refer to the wiring system diagram labeled inside the front panel.
- Check local electrical cords and also any specific wiring instructions or limitations.




**Fig. 10-2-5**




Stripping length of the connecting cable

**NOTE:**

- Use stranded wire only.
- Wire type : H07RN-F or more

### 10-2-5. Piping and drain hose installation

**<Piping and Drain Hose Forming>**

* Since dewing results in a machine trouble, make sure to insulate both the connecting pipes. (Use polyethylene foam as insulating material.)




**1. Die-cutting Front panel slit**

Cut out the slit on the left or right side of the front panel for the left or right connection and the slit on the bottom left or right side of the front panel for the bottom left or right connection with a pair of nippers.

**2. Changing drain hose**

For left connection, bottom-leftward connection and rear-leftward connection's piping, it is necessary to change the drain hose and drain cap.

**<How to remove the Drains Cap>**

Clip drain cap by needle-nose pliers, and pull out.



**Fig. 10-2-6**

**<How to install the Drain Hose>**

Firmly insert drain hose connecting part until hitting on a heat insulator.




**Fig. 10-2-7**

Downloaded from AC-Manual.com Manuals

**<How to fix the Drains Cap>**

1) Insert hexagonal wrench (∅4 mm) in a center head.




**Fig. 10-2-8**

2) Firmly insert drains cap.


No gap
Do not apply lubricating oil (refrigerant machine oil) when inserting the drain cap. Application causes deterioration and drain leakage of the plug.
Insert a hexagon wrench (∅4 mm)

**Fig. 10-2-9**

**CAUTION**

Firmly insert the drain hose and drain cap; otherwise, water may leak.

**<In case of right or left piping>**

- After scribing slits of the front panel with a knife or a making-off pin, cut them with a pair of nippers or an equivalent tool.




**Fig. 10-2-10**

**<In case of bottom right or bottom left piping>**

- After scribing slits of the front panel with a knife or a making-off pin, cut them with a pair of nippers or an equivalent tool.




**Fig. 10-2-11**

**<Left-hand connection with piping>**

Bend the connecting pipe so that it is laid within 43 mm above the wall surface. If the connecting pipe is laid exceeding 43 mm above the wall surface, the indoor unit may unstably be set on the wall. When bending the connecting pipe, make sure to use a spring bender so as not to crush the pipe.

**Bend the connection pipe within a radius of 30 mm (∅6.35) 40 mm (∅9.52).**

To connect the pipe after installation of the unit (figure)


(To the forefront of flare)
270 mm
Liquid side
170 mm
Gas side
Outward form of indoor unit
43 mm
R 30 mm or less (∅6.35) R 40 mm or less (∅9.52)
(Use polisin (polyethylene core) or the like for bending pipe.)
80°
Use the handle of screwdriver, etc.

**Fig. 10-2-12**

**NOTE:**

If the pipe is bent incorrectly, the indoor unit may unstably be set on the wall.
After passing the connecting pipe through the pipe hole, connect the connecting pipe to the auxiliary pipes and wrap the facing tape around them.

**CAUTION**

- Bind the auxiliary pipes (two) and connecting cable with facing tape tightly. In case of leftward piping and rear-leftward piping, bind the auxiliary pipes (two) only with facing tape.




**Fig. 10-2-16**

- Carefully arrange pipes so that any pipe does not stick out of the rear plate of the indoor unit.
- Carefully connect the auxiliary pipes and connecting pipes to each other and cut off the insulating tape wound on the connecting pipe to avoid double-taping at the joint, moreover, seal the joint with the vinyl tape, etc.
- Since dewing results in a machine trouble, make sure to insulate both the connecting pipes. (Use polyethylene foam as insulating material.)
- When bending a pipe, carefully do it not to crush it.

Downloaded from AC-Manual.com Manuals

### 10-2-6. Indoor unit fixing

1. Pass the pipe through the hole in the wall, and hook the indoor unit on the installation plate at the upper hooks.
2. Swing the indoor unit to right and left to confirm that it is firmly hooked up on the installation plate.
3. While pressing the indoor unit onto the wall, hook it at the lower part on the installation plate. Pull the indoor unit toward you to confirm that it is firmly hooked up on the installation plate.




**Fig. 10-2-14**

- For detaching the indoor unit from the installation plate pull the indoor unit toward you while pushing its bottom up at the specified parts.




**Fig. 10-2-15**

### 9-2-7. Drainage

1. Run the drain hose sloped downwards.

**NOTE:**

- Hole should be made at a slight downward slant on the outdoor side.


Do not rise the drain hose.
Do not form the drain hose into a wavy shape.
50 mm or more
Do not put the drain hose end into water.
Do not put the drain hose end in the drainage ditch.

**Fig. 10-2-16**

2. Put water in the drain pan and make sure that the water is drained out of doors.
3. When connecting extension drain hose, insulate the connecting part of extension drain hose with shield pipe.




**Fig. 10-2-17**

**CAUTION**

Arrange the drain pipe for proper drainage from the unit.
Improper drainage can result in dew-dropping.

This air conditioner has the structure designed to drain water collected from dew, which forms on the back of the indoor unit, to the drain pan.
Therefore, do not store the power cord and other parts at a height above the drain guide.




**Fig. 10-2-18**

Downloaded from AC-Manual.com Manuals

## 10-3. Outdoor Unit

### 10-3-1. Installation place

- A place which provides the spaces around the outdoor unit as shown in the left diagram.
- A place which can bear the weight of the outdoor unit and does not allow an increase in noise level and vibration.
- A place where the operation noise and discharged air do not disturb users neighbors.
- A place which is not exposed to a strong wind.
- A place free of a leakage of combustible gases.
- A place which does not block a passage.
- When the outdoor unit is to be installed in an elevated position, be sure to secure its feet.
- An allowable length of the connecting pipe is up 10 m.
- An allowable height level is up to 8 m.
- A place where the drain water does not raise any problem.

**CAUTION**

1. Install the outdoor unit without anything blocking the air discharging.
2. When the outdoor unit is installed in a place exposed always exposed to strong wind like a coast or on a high storey of a building, secure the normal fan operation using a duct or a wind shield.
3. In particularly windy areas, install the unit such as to avoid admission of wind.
4. Installation in the following places may result in trouble.
   Do not install the unit in such places.
   - A place full of machine oil.
   - A saline-place such as the coast.
   - A place full of sulfide gas.
   - A place where high-frequency waves are likely to be generated as from audio equipment, welders, and medical equipment.




**Fig. 10-3-1**

### 10-3-2. Refrigerant piping connection

**<Flaring>**

1. Cut the pipe with a pipe cutter.




**Fig.10-3-2**

2. Insert a flare nut into the pipe, and flare the pipe.
   **Projection margin in flaring : A (Unit : mm)**




**Fig. 10-3-3**

Rigid (Clutch type)

| Outer dia. of copper pipe | R410A tool used | Conventional tool used |
|---|---|---|
| 6.35 | 0 to 0.5 | 1.0 to 1.5 |
| 9.52 | 0 to 0.5 | 1.0 to 1.5 |

Imperial (wing nut type)

| Outer dia. of copper pipe | R410A |
|---|---|
| 6.35 | 1.5 to 2.0 |
| 9.52 | 1.5 to 2.0 |

**<Tightening connection>**

Align the centers of the connecting pipes and tighten the flare nut as far as possible with your fingers. Then tighten the nut with a spanner and torque wrench as shown in the figure.




**Fig. 10-3-4**

**CAUTION**

- Do not apply excess torque.
- Otherwise, the nut may crack depending on the conditions.

Downloaded from AC-Manual.com Manuals

(Unit : N•m)

| Outer dia. of copper pipe | Tightening torque |
|---|---|
| ∅6.35 mm | 16 to 18 (1.6 to 1.8 kgf·m) |
| ∅9.52 mm | 30 to 42 (3.0 to 4.2 kgf·m) |

**Tightening torque of flare pipe connections**

The operating pressure of R410A is higher than that of R22. (Approx. 1.6 times).
It is therefore necessary to firmly tighten the flare pipe connecting sections (which connect the indoor and outdoor units) up to the specified tightening torque. Incorrect connections may cause not only a gas leakage, but also damage to the refrigerant cycle.




**Fig. 10-3-5**

**<Shaping pipes>**

1. How to shape the pipes
   Shape the pipes along the incused line on the outdoor unit.
2. How to fit position of the pipes
   Put the edges of the pipes to the place with a distance of 85 mm from the incused line.




**Fig. 10-3-6**

### 10-3-3. Evacuating

After the piping has been connected to the indoor unit, you can perform the air purge together at once.

**AIR PURGE**
Evacuate the air in the connecting pipes and in the indoor unit using a vacuum pump. Do not use the refrigerant in the outdoor unit. For details, see the manual of the vacuum pump.

**<Using a vacuum pump>**

Be sure to use a vacuum pump with counter-flow prevention function so that inside oil of the pump does not flow backward into pipes of the air conditioner when the pump stops. (If oil inside of the vacuum pump enters into the air conditioner, which use R410A, refrigeration cycle trouble may result.)

1. Connect the charge hose from the manifold valve to the service port of the gas side packed valve.
2. Connect the charge hose to the port of the vacuum pump.
3. Open fully the low pressure side handle of the gauge manifold valve.
4. Operate the vacuum pump to start evacuating. Perform evacuating for about 15 minutes if the piping length is 20 meters. (15 minutes for 20 meters) (assuming a pump capacity of 27 liters per minute. Then confirm that the compound pressure gauge reading is -101 kPa (-76 cmHg).
5. Close the low pressure side valve handle of gauge manifold.
6. Open fully the valve stem of the packed valves (both side of Gas and Liquid).
7. Remove the charging hose from the service port.
8. Securely tighten the caps on the packed valves.




**Fig. 10-3-7**

**CAUTION**

- **KEEP IMPORTANT 4 POINTS FOR PIPING WORK**

(1) Take away dust and moisture (Inside of the connecting pipes.)
(2) Tight connection (between pipes and unit)
(3) Evacuate the air in the connecting pipes using VACUUM PUMP.
(4) Check gas leak (connected points)

Downloaded from AC-Manual.com Manuals

**<Packed valve handling precautions>**

- Open the valve stem all the way out; but do not try to open it beyond the stopper.
- Securely tighten the valve stem cap with torque in the following table:

| | |
|---|---|
| Gas side (∅9.52 mm) | 30 to 42 N·m (3.0 to 4.2 kgf·m) |
| Liquid side (∅6.35 mm) | 16 to 18 N·m (1.6 to 1.8 kgf·m) |
| Service port | 9 to 10 N·m (0.9 to 1.0 kgf·m) |




**Fig. 10-3-8**

### 10-3-4. Wiring connection

1. Remove the valve cover from the outdoor unit.
2. Connect the connecting cable to the terminal as identified with their respective matched numbers on the terminal block of indoor and outdoor unit.
3. When connecting the connecting cable to the outdoor unit terminal, make a loop as shown in the installation diagram of indoor and outdoor unit, to prevent water coming in the outdoor unit.
4. Insulate the unused cords (conductors) from any water coming in the outdoor unit. Proceed them so that they do not touch any electrical or metal parts.

**<Stripping length of connection cable>**




**Fig. 10-3-8**

| Model | 42NQV025M, 42NQV025M-A |
|---|---|
| Power source | 50 Hz, 220 - 240 V~ Single phase |
| Maximum running current | 5A |
| Installation fuse rating | 20A |
| Power cord | H07RN-F or 245 IEC66 (1.5 $mm^2$ or more) |

**CAUTION**

- Wrong wiring connection may cause some electrical parts burn out.
- Be sure to comply with local codes on running the wire from indoor unit to outdoor unit (size of wire and wiring method etc).
- Every wire must be connected firmly.
- This installation fuse (20A) must be used for the power supply line of this air conditioner.
- If incorrect or incomplete wiring is carried out, it will cause an ignition or smoke.
- Prepare the power supply for exclusive use with the air conditioner.
- This product can be connected to the mains. Connection to fixed wiring: A switch which disconnects all poles and has a contact separation of at least 3 mm must be incorporated in the fixed wiring.

**NOTE: Connecting cable**

- Wire type: More than H07RN-F or 245 IEC66 (1.0 $mm^2$ or more)

Downloaded from AC-Manual.com Manuals

### 10-3-5. Gas leak test




**Fig. 10-3-10**

- Check the flare nut connections for the gas leak with a gas leak detector or soap water.

### 10-3-6. Test operation

To switch the TEST RUN (COOL) mode, push RESET button for 10 sec.
(The beeper will make a short beep.)




**Fig. 10-3-11**

### 10-3-7. Auto restart setting

This product is designed so that, after a power failure, it can restart automatically in the same operating mode as before the power failure.

**Information**

The product was shipped with Auto Restart function in the off position. Turn it on as required.

**<How to set the auto restart>**

- Press and hold down the RESET button for about 3 seconds. After 3 seconds, the electronic beeper makes three short beeps to tell you the Auto Restart has been selected.
- To cancel the Auto Restart, follow the steps described in the section Auto Restart Function of the Owner's Manual.

### 10-3-8. Remote Controller Selector Switch Setting

**When two indoor units are installed in the separated rooms, it is not necessary to change the selector switches.**

**Remote control selector switch**

- When two indoor units are installed in the same room or adjacent two rooms, if operating a unit, two units may receive the remote control signal simultaneously and operate. In this case, the operation can be preserved by setting either one indoor unit or remote control to B setting. (Both are set to A setting in factory shipment.)
- The remote control signal is not received when the settings of indoor unit and remote control are different.
- There is no relation between A setting/B setting and A room/B room when connecting the piping and cables.

**Remote Control A-B Selection**

To separate using of remote control for each indoor unit in case of 2 air conditioner are installed nearly.
the remote control signal simultaneously and operate. In this

**Remote Control B Setup.**

1. Press RESET button on the indoor unit to turn the air conditioner ON.
2. Point the remote control at the indoor unit.
3. Push and hold button on the Remote Control by the tip of the pencil. "00" will be shown on the display.
4. Press Ⓜ during pushing , "B" will show on the display and"00" will disappear and the air conditioner will turn OFF. The Remote Control B is memorized.

**Note :** 1. Repeat above step to reset Remote Control to be A.
2. Remote Control A have not "A" display.
3. Detault setting of Remote Control from factory is A.




**Fig. 10-3-12**

Downloaded from AC-Manual.com Manuals

# 11. HOW TO DIAGNOSE THE TROUBLE

The pulse modulating circuits are mounted to both indoor and outdoor units. Therefore, diagnose troubles according to the diagnosis procedure as described below. (Refer to the check points in servicing written on the wiring diagrams attached to the indoor/outdoor units.)

**Table 11-1**

| No. | Troubleshooting Procedure |
|---|---|
| 1 | First Confirmation |
| 2 | Primary Judgement |
| 3 | Judgement by Flashing LED of Indoor Unit |
| 4 | Self-Diagnosis by Remote Controller |
| 5 | Judgement of Trouble by Every Symptom |
| 6 | How to Check Simply the Main Parts |

**NOTE:**

A large-capacity electrolytic capacitor is used in the outdoor unit controller (inverter). Therefore, if the power supply is turned off, charge (charging voltage DC280V) remains and discharging takes a lot of time. After turning off the power source, if touching the charging section before discharging, an electrical shock may be caused. Discharge the electrolytic capacitor completely by using soldering iron, etc.

**<Discharging method>**

(1) Remove the inverter cover (plating) by opening four mounting claws.
(2) As shown below, connect the discharge resistance (approx. 100Ω40W) or plug of the soldering iron to voltage between + – terminals of the C12 (“CAUTION HIGH VOLTAGE” is indicated.) electrolytic capacitor (760µF/400V) on P.C. board, and then perform discharging.




**Fig. 11-1**

## 11-1. First Confirmation

### 11-1-1. Confirmation of power supply

Confirm that the power breaker operates (ON) normally.

### 11-1-2. Confirmation of power voltage

Confirm that power voltage is AC 220-240 V ± 10%. If power voltage is not in this range, the unit may not operate normally.

Downloaded from AC-Manual.com Manuals

### 11-1-3. Operation which is not a trouble (Program operation)

For controlling the air conditioner, the program operations are built in the microcomputer as described in the following table. If a claim is made for running operation, check whether or not it meets to the contents in the following table. When it does, we inform you that it is not trouble of equipment, but it is indispensable for controlling and maintaining of air conditioner.

**Table 11-1-1**

| No. | Operation of air conditioner | Descriptions |
|---|---|---|
| 1 | When power breaker is turned “ON”, the operation lamp (Green) of the indoor unit flashes. | The OEPRATION lamp of the indoor unit flashes when power source is turned on. If [ ① ] button is operated once, flashing stops. (Flashes also in power failure) |
| 2 | Compressor may not operate even if the room temperature is within range of compressor-ON. | The compressor does not operate while compressor restart delay timer (3-minutes timer) operates. The same phenomenon is found after power source has been turned on because 3-minutes timer operates. |
| 3 | In Dry and ECONO. Mode, FAN (air flow) display does not change even though FAN (air flow select) button is operated. | The air flow indication is fixed to [AUTO]. |
| 4 | Increasing of compressor motor speed stops approx. 30 seconds after operation started, and then compressor motor speed increases again approx. 30 seconds after. | For smooth operation of the compressor, the compressor motor speed is restricted to Max. 41 rps for 2 minutes, and Max.91 rps for 2 minutes to 3 minutes, respectively after the operation has started. |
| 5 | The set value of the remote controller should be below the room temperature. | If the set value is above the room temperature, Cooling operation is not performed. And check whether battery of the remote controller is consumed or not. |
| 6 | In AUTO mode, the operation mode is changed. | After selecting Cool or Heat mode, select an operation mode again if the compressor keeps stop status for 15 minutes. |
| 7 | In HEAT mode, the compressor motor speed does not increase up to the maximum speed or decreases before the temperature arrives at the set temperature. | The compressor motor speed may decrease by high-temp. release control (Release protective operation by temp.-up of the indoor heat exchanger) or current release control. |

## 11-2. Primary Judgement

To diagnose the troubles, use the following methods.
(1) Judgement by flashing LED of indoor unit
(2) Self-diagnosis by service check remote controller
(3) Judgement of trouble by every symptom

Firstly, use the method (1) for diagnosis. Then, use the method (2) and (3) to diagnose the details of troubles.

Downloaded from AC-Manual.com Manuals

## 11-3. Judgment by Flashing LED of Indoor Unit

While the indoor unit monitors the operation status of the air conditioner, if the protective circuit operates, the contents of self-diagnosis are displayed with block on the indoor unit indication section.

Table 11-3-1




| Item | Check code | Block display | Description for self-diagnosis |
|---|---|---|---|
| A | — | OPERATION (Green)<br>Flashing display (1 Hz) | Power failure (when power is ON) |
| B | 00 | OPERATION (Green)<br>Flashing display (5 Hz) | Protective circuit operation for indoor P.C. board |
| C | 01 | OPERATION (Green)<br>TIMER (Yellow)<br>Flashing display (5 Hz) | Protective circuit operation for connecting cable and serial signal system |
| D | 02 | OPERATION (Green)<br>Flashing display (5 Hz) | Protective circuit operation for outdoor P.C. board |
| E | 03 | OPERATION (Green)<br>TIMER (Yellow)<br>Flashing display (5 Hz) | Protective circuit operation for others (including compressor) |

NOTES :

1. The contents of items B and C and a part of item E are displayed when air conditioner operates.
2. When item B and C, and item B and a part of item E occur concurrently, priority is given to the block of item B.
3. The check codes can be confirmed on the remote controller for servicing.



Downloaded from AC-Manual.com Manuals

## 11-4. Self-Diagnosis by Remote Controller (Check Code)

1. If the lamps are indicated as shown B to E in Table 11-3-1, execute the self-diagnosis by the remote controller.
2. When the remote controller is set to the service mode, the indoor controller diagnoses the operation condition and indicates the information of the self-diagnosis on the display of the remote controller with the check codes. If a fault is detected, all lamps on the indoor unit will flash at 5Hz and it will beep for 10 seconds (Beep, Beep, Beep ... ). The timer lamp usually flashes (5Hz) during self-diagnosis.

### 11-4-1. How to Use Remote Controller in Service Mode




Alphanumeric characters are used for the check codes.

| | |
|---|---|
| 5 is 5. | 6 is 6. |
| A is A. | b is B. |
| C is C. | d is D. |

**1** **Press [ ] button with a tip of pencil to set the remote controller to the service mode.**

- " 00 " is indicated on the display of the remote controller.

**2** **Press [ ] or [ ] button**

If there is no fault with a code, the indoor unit will beep once (Beep) and the display of the remote controller will change as follows :

00 → 01 → 02 ··· 1d → 1E → 33

- The TIMER indicator of the indoor unit flashes continuously. (5 times per 1 sec.)
- Check the unit with all 52 check codes ( 00 to 33 ) as shown in Table-11-4-1.
- Press [ ] or [ ] button to change the check code backward.

If there is a fault, the indoor unit will beep for 10 seconds (Beep, Beep, Beep...).

Note the check code on the display of the remote controller.

- 2-digits alphanumeric will be indicated on the display.
- All indicators on the indoor unit will flash. (5 times per 1 sec.)

**3** **Press [ ] button to release the service mode.**

- The display of the remote controller returns to as it was before service mode was engaged.

**4** Time shortening method.

1. Press button while pushing button.
2. Press [ ] button.

**Fig. 11-4-1**



Downloaded from AC-Manual.com Manuals

### 11-4-2. Caution at servicing

(1) After servicing, push the [ ⏻ ] button to return to the normal mode.
(2) After servicing by the check code, turn off breaker of the power supply, and turn on breaker of the power supply again so that memory in the microcomputer returns the initial status. However, the check codes are not deleted even if the power supply is turned off because they are stored in the fixed memory.

**Table 11-4-1**

| Block distinction | | Operation of diagnosis function | | | | Judgement and action |
|---|---|---|---|---|---|---|
| Check code | Block | Check code | Cause of operation | Air conditioner status | Remark | |
| 00 | Indoor P.C. board | 0C | Short-circuit or disconnection of the room temperature sensor (TA sensor). | Operation continues. | Displayed when error is detected. | 1. Check the room temp. sensor.<br>2 When the room temp. sensor is normal, check P.C. board. |
| | | 0d | Being out of place, disconnection, short-circuit, or migration of heat exchanger sensor (TC sensor) | Operation continues. | Displayed when error is detected. | 1. Check heat exchanger sensor.<br>2. When heat exchanger sensor is normal, check P.C. board. |
| | | 11 | Lock of indoor fan or trouble on the indoor fan circuit | All off | Displayed when error is detected. | 1. Check P.C. board.<br>2. When P.C. board is normal, check the motor. |
| | Not displayed | 12 | Trouble on other indoor P.C. boards | Operation continues. | Displayed when error is detected. | Replace P.C. board. |
| 01 | Connecting cable and serial signal | 04 | Return serial signal is not sent to indoor side from operation started.<br>(1) Defective wiring of connecting cable<br>(2) Operation of compressor thermo.<br>Gas shortage<br>Gas leak | Operation continues. | Flashes when trouble is detected on Return serial signal, and normal status when signal is reset. | 1. When the outdoor unit never operate:<br>(1) Check connecting cable, and correct if defective wiring.<br>(2) Check 25A fuse of inverter P.C. board<br>(3) Check 3.15A of inverter P.C. board.<br>2. To display [Other] block during operation, check compressor thermo. operation and supply gas (check gas leak also).<br>3. Unit operates normally during check.<br>If Return serial signal does not stop between ② and ③ of the indoor terminal block, replace inverter P.C. board. If signal stops between ② and ③ of the indoor terminal block, replace indoor P.C. board. |
| | | 05 | Operation command signal is not sent to outdoor side. | Operation continues. | Flashes when trouble is detected on Operation command signal, and normal status when signal is reset. | If Return serial signal does not stop between ② and ③ of the indoor terminal block, replace inverter P.C. board. If signal stops between ② and ③ of the indoor terminal block, replace indoor P.C. board. |

Downloaded from AC-Manual.com Manuals

| Block distinction | | Operation of diagnosis function | | | | Judgement and action |
|---|---|---|---|---|---|---|
| Check code | Block | Check code | Cause of operation | Air conditioner status | Remark | |
| 02 | Outdoor P.C. board | 14 | Inverter over-current protective circuit operates. (Short time) | All off | Displayed when error is detected. | Even if trying operation again, all operations stop immediately. : Replace P.C. board. |
| | | 16 | Position-detect circuit error or short-circuit between windings of compressor | All off | Displayed when error is detected. | 1. Even if connecting lead wire of compres sor is removed, position-detect circuit error occurred. : Replace P.C. board.<br>2. Measure resistance between wires of compressor, and perform short circuit. : Replace compressor. |
| | | 17 | Current-detect circuit error | All off | Displayed when error is detected. | Even if trying operation again, all operations stop immediately. : Replace P.C. board. |
| | | 18 | Being out of place, disconnection or short-circuit of outdoor temp. sensor | All off | Displayed when error is detected. | 1. Check outdoor temp. sensors (TE).<br>2. Check P.C. board. |
| | | 19 | Disconnection or short-circuit of discharge temp. sensor | All off | Displayed when error is detected. | 1. Check discharge temp. sensor (TD).<br>2. Check P.C. board. |
| | | 1A | Outdoor fan drive system error | All off | Displayed when error is detected. | Position-detect error, over-current protective operation of outdoor fan drive system, fan lock, etc. : Replace P.C. board or fan motor. |
| | Not displayed | 1b | Outdoor heat exchanger temp. sensor error | Operation continues | —— | 1. Check outdoor heat exchanger temp. sensor (TE).<br>2. Check P.C. board. |
| | Outdoor P.C. board | 1C | Compressor drive output error, Compressor error (lock, missing, etc.), Break down | All off | Displayed when error is detected. | When 20 seconds passed after start up, position-detect circuit error occurred. : Replace compressor. |
| 03 | Others (including compres-sor) | 07 | Return serial signal has been sent when operation started, but it is not sent from halfway.<br>(1) Compressor thermo. operation Gas shortage Gas leak<br>(2) Instantaneous power failure | Operation continues | Flashes when trouble is detected on Return serial signal, and normal status when signal is reset. | 1. Repeat Start and Stop with interval of approx. 10 to 40 minutes. (Code is not displayed during operation.) Supply gas. (Check also gas leak.)<br>2. Unit operates normally during check. If Return serial signal does not stop between ② and ③ of the indoor terminal block, replace inverter P.C. board. If signal stops between ② and ③ of the indoor terminal block, replace indoor P.C. board. |
| | | 1d | Compressor does not rotate. (Current protective circuit does not operate when a specified time passed after compressor had been activated.) | All off | Displayed when error is detected. | 1. Trouble on compressor<br>2. Trouble on wiring of compressor (Missed phase) |
| | | 1E | Discharge temp. exceeded 117°C | All off | Displayed when error is detected. | 1. Check discharge temp. sensor (TD).<br>2. Degassing<br>3. Trouble on P.M.V. |
| | | 1F | Break down of compressor | All off | Displayed when error is detected. | 1. Check power voltage. (220-240 V + 10%)<br>2. Overload operation of refrigeration cycle<br>Check installation condition (Short-circuit of outdoor diffuser.) |
| | | 08 | Four-way valve inverse error (TC sensor value lowered during heating operation.) | Operation continues | —— | 1. Check 4 way valve operation. |

Downloaded from AC-Manual.com Manuals

## 11-5. Judgement of Trouble by Every Symptom

### 11-5-1. Indoor unit (Including remote controller)

**(1) Power is not turned on (Does not operate entirely)**


Turn off power supply once, and 5 second later, turn it on again.
Is OPERATION lamp blinking?
NO
YES
Is it possible to turn on power supply by pressing [⏻] button on remote control?
NO
Does transmission mark on remote control flash normally, and is its signal transmitted properly?
NO
Remote control is defective.
Refer to (5) "Troubleshooting for Remote Control."
YES
YES
Unit operates normally.
Is fuse (F01) of indoor control board blown?
YES
Parts (D01, D04, C03, T101 and IC12) are defective.
Does fan motor connector between 1 and ③ short-circuit?
YES
NO
Is voltage (DC 12V or 5V) indicated on rear of indoor control board normal?
NO
YES
Microcomputer is defective.
Replace main P.C. board.
Is the voltage across C03 measured DC 310V~340V?
NO
Refer to <Primary check> or this problem is one step short of power P.C. board block.
YES
Are DC 5V, DC 12V supplied to main P.C. board?
NO
Turn off breaker once and turn it on again after removing motor.
Are DC 5V, or DC 12V supplied to main P.C. board?
NO
Regulator IC (IC12) or T101 are defective
YES
YES
Replace motor
Operation
Check item
Conceivable principle cause
Measure
Item by symptoms

- Be sure to disconnect the motor connector CN10 after shut off the power supply, or it will be a cause of damage of the motor.

Downloaded from AC-Manual.com Manuals

**(2) Power is not turned on though Indoor P.C. board is replaced**

**<Confirmation procedure>**




Downloaded from AC-Manual.com Manuals

**(3) Only the indoor fan does not operate.**

**<Check procedure>**


Shut off the power supply once.
Turn the power supply.
Does the fan stop in no operating status?
NO
Control P.C. board is defective.
Replace the P.C. board.
YES
Start the operation with low fan setting in cool operation.
Does the fan rotate?
NO
Does AC 120 V or higher voltage apply to between red and black lead of fan motor?
NO
Does connecting terminal, connecting cable or power supply cord completely? Does not found the short wire about connecting cable and power cord?
NO
YES
YES
YES
Shut off the power supply.
Change the setting of cooling to high fan.
Does the cross flow fan rotate normally?
NO
Repair the bearing of the fan.
YES
Turn on the power supply.
Motor control circuit failure (IC31, D301) or 12 V switching module failure (T101).
Does the fan speed become higher?
NO
Operation stops
YES
Replace the P.C. board.
Is the rotation signal (DC+5 V–0 V) output between ② (gray lead wire) and ③ (brown lead wire) of the motor connector (CN11) when rotating the cross flow fan by hand in no operating status? (1 pulse/one turn)
NO
Replace the fan motor.
YES
Normal
Replace the control P.C. board.
Replace connecting the cable (or power cord), and terminal block.

Downloaded from AC-Manual.com Manuals

### (4) Troubleshooting for remote control


Press [⏻] button.
The unit does not beep at all. OPERATION lamp on indoor unit is not indicated.
Is transmission mark indicated?
NO
YES
Press RESET button on remote control with tip of pencil.
Is receiver on indoor unit exposed to direct sunlight?
NO
YES
Is there any thyristor fluorescent light nearly?
NO
YES
NO
Does indoor unit operate when moving remote control near receiver or indoor unit?
YES
Batteries are exhausted.
Press [⏻] button.
Does indoor unit start to operate by automatic restart function?
NO
YES
Is transmission mark indicated?
NO
YES
NO
Does indoor unit beep and operate?
YES
Does radio sound is affected by remote control when a signal is transmitted at distance of 5 cm from radio?
NO
YES
Remote control is defective.
P.C. board is defective.
Avoid direct sunlight.
Keep indoor unit away from thyristor fluorescent light.
Replace P.C. board.
Replace batteries.
Normal operation
Replace remote control.
Note : After replacing batteries, press the RESET button with a tip of a pencil.

Downloaded from AC-Manual.com Manuals

### 11-5-2. Wiring Failure (Interconnected and serial signal wire)

**(1) Outdoor unit does not operate.**

1) Is the voltage between ② and ③ of the indoor terminal block varied?
Confirm that transmission from indoor to outdoor is correctly performed based on the following diagram.

**NOTE:**

- Measurement should be performed 2 minutes and 30 seconds after starting operation.
- Be sure to prepare a diode for judgment.




Normal time : Voltage swings between DC15V and 60V.
Abnormal time : Voltage does not vary.

**(2) Outdoor unit stops in a little while after operation started.**

**<Check procedure> Select phenomena described below.**

1) The outdoor unit stops 10 to 20 minutes after operation started, and 10 minutes or more are required to restart the unit.




2) If the unit stops once, it dose not operate until the power is turned on again.




3) The outdoor unit stops 10 minutes to 1 hour after operation started, and an alarm is displayed.
(Discharge temp. error check code 03, 1E Sensor temp. error check code 02, 1C)


Gas leak
Miswiring of connecting wires of indoor/outdoor units
Clogging of pipe and coming-off TC sensor
Refer to the chart in 10-6

Downloaded from AC-Manual.com Manuals

## 11-6. Check Code 1C (Miswiring in indoor/outdoor units) and 1E

**<Check procedure>**


Operation
Check item
Conceivable principle cause
Measure
Item by symptoms
1C
Gas leakage, disconnection of TS/TC sensors (Check code 02, 1C)
1E
Discharge temp. error, gas leakage (Check code 03, 1E)
Valve drive check
Is connector of coil connected to inverter?
NO
Set it correctly.
YES
Is positioning sound of valve (sound hitting to stopper) heard from valve when the air conditioner starts the operation after turning off power of the air conditioner once?
NOTE:
After all the operations stopped by the remote controller, the power keeps being supplied to outdoor unit for approx. 3 minutes. If operating the air conditioner by remote controller again just after all the operations stopped by the remote controller, positioning of the valve is not performed when outdoor unit is activated because supplying power to the outdoor unit is not interrupted. After positioning of the valve, activate the compressor and the outdoor fan. It takes approx. 7 seconds for positioning of the valve, and sound ticktack (hitting sound to stopper) is heard for approx. 0.5 seconds at least of that period. As the sound is low, check sound by using screwdriver, etc.
Replace coil valve.
YES
Are temp. sensors of indoor/outdoor units correctly set to the holder?
NOTE:
The temperature sensors which are used to control electronic control valve include indoor heat exchanger sensor (TC), outdoor heat exchanger temp. sensor (TE).
Set it correctly.
YES
Gas amount check and valve clogging check
Remove TC sensor connector from the P.C. board in indoor unit.
(Remove connector from the P.C. board.) Operate the air conditioner in COOL mode by TEMP button (“Pi” sound is heard if keeping pushed for 10 seconds.) The operation enters temporary operation mode which fixes opening degree of P.M.V. and No. of revolution of compressor. Check condensation at outlet of P.M.V., and then check operating pressure from the service port.
Existence of condensation at outlet of P.M.V. If there is condensation at outlet (1/4 inch = ∅6.35 mm valve side), the valve is clogged.
YES
Replace valve.
Check the operating pressure from service port, and add gas if pressure is low.
Add gas.

Downloaded from AC-Manual.com Manuals

| Diagnosis/Process flowchart | Item | Contents | Summary |
|---|---|---|---|
|  | Check<br><br><br><br><br><br><br>Operation<br><br><br><br><br>Check | Check winding resistance between phases of compressor, and resistance between outdoor frames by using a tester.<br>• Is not grounded.<br>• Is not short-circuited between windings.<br>• Winding is not opened.<br><br>Remove connector CN300 of the outdoor fan motor turn on the power breaker, and perform the operation. (Stops though activation is prompted.) Check operation within 2 minutes 20 seconds after activation stopped. | → OK if 10MΩ or more<br>→ OK if 0.51Ω → 0.57Ω (Check by a digital tester.) |

## 11-8. How to Check Simply the Main Parts

### 11-8-1. How to check the P.C. board (Indoor unit)

**(1) Operating precautions**

1) When removing the front panel or the P.C. board, be sure to shut off the power supply breaker.
2) When removing the P.C. board, hold the edge of the P.C. board and do not apply force to the parts.
3) When connecting or disconnecting the connectors on the P.C. board, hold the whole housing. Do not pull at the lead wire.

**(2) Inspection procedures**

1) When a P.C. board is judged to be defective, check for disconnection, burning, or discoloration of the copper foil pattern or this P.C. board.
2) The P.C. board consists of the following 2 parts
   **a. Main P.C. board part:**
   DC power supply circuit (5V, 12V), Indoor fan motor control circuit, CPU and peripheral circuits, buzzer, and Driving circuit of top/bottom louvers.
   **b. Indication unit of infrared ray receiving Infrared ray receiving circuit, LED:**
   To check defect of the P.C. board, follow the procedure described below.

Downloaded from AC-Manual.com Manuals

**(3) Checking procedure.**

**Table 11-6-1**

| No. | Procedure | Check Point (Symptom) | Causes |
|---|---|---|---|
| 1 | Shut off the power supply and remove the P.C. board assembly from the electronic parts base. Remove the connecting cable from the terminal block. | 1. Is the fuse blown? | 1. Application of shock voltage. Overload by short-circuit of the parts. |
| 2 | Remove the connector for the motor, and turn the power on. If the OPERATION lamp blinks (0.5 sec. : ON, 0.5 sec. : OFF) when the power turning on, the checking points described as 1-4 of right column are not necessary to perform. | Voltage check<br>1. Between F01 and CN01(pin1) (AC 220 ~ 240 V)<br>2. Between + and − of C03 (DC310 ~ 340V)<br>3. Between 5V and GND<br>4. Between 12V and GND | 1. AC power cord is defective. Poor contact of the terminal plate.<br>2. Capacitor (C121) is defective. Line filter (L01) is defective. Capacitor (C03) is defective. Diode (D01, D02, D03 or D04) is defective.<br>3. T101 is defective. |
| 3 | Start the operation with the system which the time of the restart delay timer is shortened. | 1. All indicators light for 3 sec..<br>2. Indicators do not indicate normally after approximate 3 sec.. | } Defective indicator, or poor housing assembly. (CN21) |
| 4 | Make the operation status by pressing once the [⏻] button.<br>1. The time of the restart delay timer is shortened.<br>2. Cool operation<br>3. Air volume [AUTO]<br>4. Make the setting temperature lower enough than room temperature.<br>5. Continuous operation. | 1. Compressor does not operate.<br>2. OPERATION lamp blinks. | 1. The temperature of the indoor heat exchanger is abnormally lower.<br>2. Poor contact of the heat exchanger sensor. (The connector is disconnected.) (CN62)<br>3. Heat exchanger sensor, main P.C. board are defective. (Refer to<br>4. Main P.C. board is defective. |
| 5 | The status of No. 4 is continued, and make the following condition.<br>1. Heat operation<br>2. Make the setting temperature higher enough than room temperature. | 1. Compressor does not operate.<br>2. OPERATION lamp blinks. | 1. The temperature of the heat exchanger is abnormally high.<br>2. The heat exchanger sensor connector has short-circuit. (CN62)<br>3. The heat exchanger sensor is defective.<br>4. P.C. board is defective. |
| 6 | Turn the power on after connecting the motor connector. Start the operation with the following condition.<br>1. Operation [Cooling]<br>2. Airflow [High fan]<br>3. Continuous operation | 1. Motor does not rotate. (The key operation is accepted.)<br>2. The Motor rotates, but it vibrates too much. | 1. Poor contact of the motor connector.<br>2. Fan motor is defective |



Downloaded from AC-Manual.com Manuals

## 11-7. How to Diagnose Trouble in Outdoor Unit

### 11-7-1. Summarized inner diagnosis of inverter assembly

| Diagnosis/Process flowchart | Item | Contents | Summary |
|---|---|---|---|
| Remove connector of compressor. | Preparation | Turn "OFF" the power breaker, and remove 3P connector which connects inverter and compressor. | |
| Check 25A fuse (Part No.F01). NG → Replace fuse. → Check electrolytic capacitor, diode block (DB01), etc. OK | Check | • Check whether 25A fuse on the control board assembly is blown or not. (F01) | If fuse was blown, be sure to check the electrolytic capacitor and diode block. (DB01)<br>• Connect discharge resistance (approx. 100Ω40W) or soldering iron (plug) between +, – terminals of the electrolytic capacitor (500μF) of C12 (with printed CAUTION HIGH VOLTAGE) on P.C. board. |
| Check terminal voltage of electrolytic capacitor. NG → Check electrolytic capacitor, diode (DB01), etc. OK | | |  <br>If 15A fuse is blown, discharge both edges of the electrolytic capacitor with soldering iron. |
| Does outdoor fan rotate? NO → Does LED on control board flash or go on? YES / NO | Operation<br>Measurement | Turn on power breaker, and operate the air conditioner in COOL mode by short-circuit of the timer.<br>Measure terminal voltage of the electrolytic capacity. | |
| | | 500μ F: 400WV x 2 | OK if 500μF → DC280 to 320V |
| Remove connector CN300 of outdoor fan motor, and using a tester, check resistance value between every phase at motor side. NG → Replace outdoor fan motor. OK | Check<br>Stop | After operation, turn off the power breaker after 2 minutes 20 seconds passed, and discharge the electrolytic capacity by soldering iron. Check voltage between motor phases. | Remove CN300 by pushing the part (an arrow indication) because CN300 is a connector with lock. |
| A B C | Check Measurement | • Is not winding between ①-②, ②-③, or ①-③ opened or short-circuited?<br>• Is not frame grounded with ①, ② or ③? |  <br>→ Resistance between phases should be approx. 55 to 77Ω<br>→ Should be 10MΩ or more |

Downloaded from AC-Manual.com Manuals

### 11-8-2. P.C. board layout

**Sensor characteristic table**




TD : Discharge temp. sensor
TA : Room Temperature sensor
TC : Heat exchanger temp. sensor
TO : Outdoor temp. sensor
TE : Outdoor heat exchanger temp. sensor

Downloaded from AC-Manual.com Manuals

### 11-8-3. Indoor unit (Other parts)

| No. | Part name | Checking procedure |
|---|---|---|
| 1 | Room temp. (TA) sensor<br>Heat exchanger (TC) sensor | Disconnect the connector and measure the resistance value with tester. (Normal temp.)<br>Temperature / Sensor: 10°C: TA, TC (kΩ) 20.7; 20°C: 12.6; 25°C: 10.0; 30°C: 7.9; 40°C: 4.5 |
| 2 | Remote controller | To item of How to judge whether remote controller is good or bad of the Judgement of trouble by symptom. |
| 3 | Louver motor<br>24BYJ48 | Measure the resistance value of each winding coil by using the tester. (Under normal temp. 25°C)<br>  <br>Position: 1 to 4, 1 to 6, 2 to 3, 2 to 5 — Resistance value: 380±40Ω |
| 4 | Indoor fan motor | Since judgement of AC motor is difficult on the single motor, refer to 10-5-1. (3). |

### 11-8-4. Outdoor unit (38NYV025M, 38NYV025M-A)

| No. | Part name | Checking procedure |
|---|---|---|
| 1 | Compressor<br>(Model : DA89X1C-23FZ) | Measure the resistance value of each winding by using the tester.<br>  <br>Position: Red - White 1.1Ω; White - Black 1.1Ω; Black - Red 1.1Ω<br>Under 20°C |
| 2 | Outdoor fan motor<br>(Model : SKF-240-20B-1) | Measure the resistance value of winding by using the tester.<br>  <br>1 : White 4 : –<br>2 : – 5 : –<br>3 : Red 6 : Black<br>Position: White - Black 260.1Ω; Black - Red 235.2Ω<br>At 20°C<br>For details, refer to Section 10-9. |
| 3 | Outdoor temperature sensor (TO), outdoor heat exchanger temperature sensor (TE) | Disconnect the connector, and measure resistance value with the tester. (Normal temperature)<br>TGa : Heat pump model only.<br>TO, TE : Refer to the TA, TC characteristic table in Indoor. |

Downloaded from AC-Manual.com Manuals

**11-8-6. Checking method for each part**

<table>
<tr><th>No.</th><th>Part name</th><th>Checking procedure</th></tr>
<tr><td>1</td><td>Electrolytic capacitor (For raising pressure, smoothing)</td><td>1. Turn OFF the power supply breaker.<br>2. Discharge all four capacitors completely.<br>3. Check that safety valve at the bottom of capacitor is not broken.<br>4. Check that vessel is not swollen or exploded.<br>5. Check that electrolytic liquid does not blow off.<br>6. Check that the tester shows the normal charging characteristics in continuity test.<br> 

<table><tr><th>Case that product is good</th></tr><tr><td>Pointer swings once, and returns slowly. When performing test once again under another polarity, the pointer should return.</td></tr></table>
C12, C13, C14 → 500μF/400V</td></tr>
<tr><td>2</td><td>Rectifier</td><td>1. Turn OFF the power supply breaker.<br>2. Discharge all three capacitors completely.<br>3. Check that the normal rectification characteristics are show in continuity test by the tester.<br> 



Diode check
<table>
<tr><th colspan="2">Tester rod</th><th rowspan="2">Resistance value in good product</th></tr>
<tr><th>⊕</th><th>⊖</th></tr>
<tr><td>~1</td><td rowspan="2">⊖</td><td rowspan="4">50kΩ or more<br>(0Ω in trouble)</td></tr>
<tr><td>~2</td></tr>
<tr><td rowspan="2">⊕</td><td>~1</td></tr>
<tr><td>~2</td></tr>
</table></td></tr>
</table>

Downloaded from AC-Manual.com Manuals

## 11-9. How to Simply Judge Whether Outdoor Fan Motor is Good or Bad

### 1. Symptom

- Outdoor fan motor does not rotate.
- Outdoor fan motor stops within several ten seconds though it starts rotating.
- Outdoor fan motor rotates or does not rotate according to the position where the fan stopped., etc.

### 2. Cause

The following causes are considered when the outdoor fan motor does not normally rotate.

1) Mechanical lock of the outdoor fan motor
2) Winding error of the outdoor fan motor
3) Motor drive circuit error of the outdoor P.C. board

### 3. How to simply judge whether outdoor fan motor is good or bad


Turn OFF the breaker.
Disconnect two connectors (CN300) of the outdoor fan motor from the inverter.
Does the fan rotate without trouble when rotating it with hands?
NO
YES
If the resistance value between the connector (CN300 : Motor winding) is 70 to 150Ω, it is normal.
NO
YES
Fan motor is normal.
(Outdoor P.C. board error)
Fan motor error




**NOTE :**

However, GND circuit error inside of the motor may be accepted in some cases when the above check is performed.
When the fan motor does not become normal even if P.C. board is replaced the outdoor fan motor.

Downloaded from AC-Manual.com Manuals

# 12. PART REPLACEMENT

## 12-1. Indoor Unit

| No. | Part name | Procedures | Remarks |
|---|---|---|---|
| ① | Front panel | How to remove the front panel<br>1) Stop the operation of the air conditioner and turn off its main power supply.<br>2) Pull the air inlet grille toward you to open it and remove the air inlet grille. Then remove the 2 screws fixing the front panel.<br>3) First open the horizontal louver, and then remove the front panel from the back body by pulling it toward you.<br>How to mount the front panel<br>Push the front panel back in and make sure all hooks are locked. |  |
| ② | Electrical part | How to remove the electrical part.<br>1) Remove the front panel with procedure ①.<br>2) Remove the screw holding the electrical part cover.<br>3) Disconnect the 3 connectors 2-(3P) for the fan motor and the connector (5P) for the louver motor from the P.C. board assembly.<br>4) Pull out the TC sensor from the sensor holder.<br>5) Remove the screw for the ground connection, remove the screw for the electrical part box. Then remove the LED and the electrical part box from the main unit.<br>How to mount the electrical part.<br>1) To put back the electrical part box, lock it to the upper hook of the back body.<br>2) Tighten the screws on the electrical part box.<br>3) Connect the 3 connectors and arrange the wiring same as original condition and then tighten the screw from the LED unit to the back body.<br>4) Attach the TC sensor to the holder.<br>5) Tighten the screw for the ground connection.<br>6) Tighten the screw on the electrical part cover. |  |
| ③ | Horizontal louver | 1) Remove the front panel and the electrical part following procedure ②.<br>2) Remove the center shaft of the horizontal louver from the back body.<br>3) Remove the left shaft from the back body.<br>4) Remove the horizontal louver from the back body. |  |

Downloaded from AC-Manual.com Manuals

| No. | Part name | Procedures | Remarks |
|---|---|---|---|
| ④ | Heat exchanger | 1) Remove the front panel, electrical part and the horizontal louver following procedure ③.<br>2) Remove the pipe holder at the rear side of main unit.<br>3) Remove the 2 screws on the heat exchanger at the base bearing.<br>4) Remove the screw on the heat exchanger at the fixed plate from the back body and then pull out the right hand side until the socket of heat exchanger released from the hook of the band motor (L), and then pull out the upper side of heat exchanger slowly. | <br>② Pipe holder<br>  <br>③ 2-Screws<br>  <br>④Screws |
| ⑤ | Cross flow fan | 1) Remove the front panel, electrical part, horizontal louver and the heat exchanger following procedure ④.<br>2) Remove the 2 screws on the band motor (L) and remove the 2 screws on the band motor (R) and then remove the cross flow fan.<br>3) Loosen the set screw of the cross flow fan then separate the fan and the fan motor.<br><br>Notice<br>To assemble cross flow fan and fan motor to the unit, please turn the fan motor unit the center of its terminal meets the top position of band motor (R).<br>Fix the cross flow fan with the set screw at the position where the gap between the back body and the right surface of the cross flow fan is 4.7 mm. |  <br>2-Screws (R)<br>②<br>②2-Screws (L)<br>4.7 mm<br>  <br>⑥ Set screw<br>Middle of the fan motor terminal<br> |
| ⑥ | Base bearing | 1) Remove the front panel, electrical part, horizontal louver, heat exchanger and the cross flow fan following procedure ⑤.<br>2) Remove the 2 screws fixing the base bearing.<br>3) Remove the bearing from the base bearing. If the housing protrudes from the base bearing, put the housing in position and attach the bearing to the base bearing. |  <br>② 2-Screws |

Downloaded from AC-Manual.com Manuals

## 12-2. Microcomputer

| No. | Part name | Procedures | Remarks |
|---|---|---|---|
| ① | Common procedure | 1) Turn the power supply off to stop the operation of air conditioner.<br>2) Remove the front panel.<br>• Remove the 4 fixing screws.<br>3) Remove the electrical part base. | Replace the thermal fuse, terminal block, microcomputer ass'y and the P.C. board ass'y |

**<P.C. board layout>**




**Top View**

Downloaded from AC-Manual.com Manuals

**<P.C. board layout>**




**Solder side**

Downloaded from AC-Manual.com Manuals

## 12-3-1. Outdoor Unit

| No. | Part name | Procedures | Remarks |
|---|---|---|---|
| ① | Common procedure | **1. Detachment**<br>1) Stop operation of the air conditioner, and turn off the main switch and breaker of the air conditioner.<br>2) Remove the valve cover. (ST1TØ4 x 10ℓ 1 pc)<br>• After removing screw, remove the valve cover pulling it downward.<br>3) Remove the wiring cover (ST1TØ4 x 10ℓ 2 pcs.), and then remove the power cord, connecting cable, and cord clamp (ST2TØ4 x 16ℓ 3 pcs.).<br>4) Remove the upper cabinet. (ST1TØ4 x 10ℓ 5 pcs.)<br>• After removing screws, remove the upper cabinet pulling it upward.<br><br>**2. Attachment**<br>1) Attach the upper cabinet. (ST1TØ4 x 10ℓ 5 pcs.)<br>• Hook the rear side of the upper cabinet to the claw of the rear cabinet, and then place it on the front cabinet.<br>2) After connecting the power cord and connecting cable, attach the cord clamp and wiring cover.<br>• Insert the upper part into the upper cabinet, and insert the claw which has been hooked to the lower part into the square hole, and then fix it with screw. (ST1TØ4 x 10ℓ 1 pc.)<br>3) Attach the valve cover. (ST1TØ4 x 10ℓ 1 pc.)<br>• Insert the upper part to the upper cabinet, set the hook claw of the valve cover to square holes (at three positions) of the main unit, and attach it pushing upward. |  <br>  |
| ② | Front cabinet | **1. Detachment**<br>1) Perform work of item 1 of ①.<br>2) Remove upper screw (ST1TØ4 x 10ℓ 4 pcs.) of the front cabinet, and lower screws (ST1TØ4 x 10ℓ 8 pcs.) of the front cabinet.<br>• Both side of front cabinet envelop the unit, so remove it by pulling sideward.<br><br>**2. Attachment**<br>1) Assemble front cabinet to the unit.<br>2) Attach the removed screws to the original positions. |  |

Downloaded from AC-Manual.com Manuals

| No. | Part name | Procedures | Remarks |
|---|---|---|---|
| ③ | Inverter assembly | 1) Perform work of item 1 of ①.<br>2) Remove screw (ST1T∅4 x 10ℓ 1 pc.) of the upper part of the front cabinet.<br>• If removing the inverter cover in this condition, the P.C. board can be checked.<br>• If there is no space in the upper part of the upper cabinet, perform work of ②.<br>**Be careful when checking the inverter because high-voltage circuit is incorporated in it.**<br>3) Perform discharging by connecting the ⊕,⊖ polarities by discharging resistance (approx. 100Ω40W) or plug of soldering iron to ⊕,⊖ terminals of the C13 (printed "CAUTION HIGH VOLTAGE" is attached.) electrolytic capacitor (760 µF/400 WV) on the P.C. board.<br>**Be careful to discharge the capacitor because the electrolytic capacitor cannot naturally discharge and voltage remains depending on the malfunction state in some cases.**<br>**NOTE :**<br>**This capacitor has mass capacity. Therefore, it is dangerous that a large spark generates if short-circuiting between the ⊕,⊖ polarities with screwdriver, etc. for discharging.**<br>4) Perform the work of ②.<br>5) Remove the screw (ST1T∅4 x 10ℓ 1 pc.) fixing the main body and the inverter box.<br>6) Remove the lead wire from the holder on the terminal block.<br>7) Disconnect the connectors of various lead wires.<br>**Requirement :**<br>**As each connector has a lock mechanism, avoid removing the connector by holding the lead wire, but by holding the connector.** |  <br>  <br>  <br>The connector is one with lock, so remove it while pushing the part indicated by an arrow.<br>  <br>  <br>Be sure to remove the connector by holding the connector, not by pulling the lead wire. |

Downloaded from AC-Manual.com Manuals

| No. | Part name | Procedures | Remarks |
|---|---|---|---|
| ④ | Control board assembly | 1) Disconnect lead wires and connectors connected from the control board assembly to other parts.<br>1. Lead wires<br>• Connection with terminal block : 3 wires (Black, White, Orange)<br>• Connection with compressor : remove the connector (3P)<br>• Connection with reactor : remove the connector (2P)<br>2. Connectors (6 positions)<br>CN300, CN703 : Outdoor fan (3P: white)* (See Note 1)<br>CN701 : 4 way valve (3P: Yellow)*<br>CN601 : TD sensor (2P: White)<br>CN602 : TO sensor (2P: White)<br>CN500 : Case thermo (2P: White)<br>* Note 1) As the connector has a stopper, release the housing lock when removing.<br>** Note 2) Hold the housing (resin part) with stopper and pull out to remove.<br>2) Remove the control board assembly from the inver ter box.<br>Note 2) Remove the claw of the board support fixed to the inverter board, and remove upwards holding the heat sink.<br>3) Remove the three screws fixing the heat sink and control board assemble.<br>4) Attach the new contro board assembly.<br>Note 4) When attaching the new control board assembly. insert the P.C. board into the guide rail groove correctly. |  <br>As CN300 and CN701 are connectors with lock, remove while pushing the part indicated by an arrow<br>  |

Downloaded from AC-Manual.com Manuals

| No. | Part name | Procedures | Remarks |
|---|---|---|---|
| ③ | Fan motor | 1) Perform work of item 1 of ① and 1 of ②.<br>2) Remove the flange nut fixing the fan motor and the propeller fan.<br>• Flange nut is loosened by turning clockwise.<br>(To tighten the flange nut, turn counter-clockwise.)<br>3) Remove the propeller fan.<br>4) Disconnect the connector for the fan motor from the inverter.<br>5) Remove the fixing screws (4 pcs.) holding the fan motor by hand so that it does not fall.<br>6) Cut the motor lead at the point which is 100 mm apart from the connector toward the fan.<br>7) Use the connector used for the inverter, and pinch the lead wires using the closed end splice. |  |
| ④ | Compressor | 1) Perform work of item 1 of ①, 1 of ② and ③.<br>2) Extract refrigerant gas.<br>3) Remove the partition board.<br>(ST1TØ4 x 10ℓ 3 pcs.)<br>4) Remove the sound-insulation material.<br>5) Remove the terminal cover of the compressor, and disconnect the lead wire of the compressor thermo and the compressor from the terminal.<br>6) Remove the pipe connected to the compressor with a burner.<br>• Make sure the flame does not touch the 4 way valve.<br>7) Remove the fixing screw of the base plate and heat exchanger.<br>(ST1TØ4 x 10ℓ 2 pcs.)<br>8) Pull upward the refrigeration cycle.<br>9) Remove the nut fixing the compressor to the base plate. |  |
| ⑤ | Reactor | 1) Perform work of item 1 of ①, 1 of ②, and ③.<br>2) Remove the screw fixing the reactor.<br>(ST1TØ 4 x 10ℓ 2 PCS.) |  |

Downloaded from AC-Manual.com Manuals

| No. | Part name | Procedures | Remarks |
|---|---|---|---|
| ⑥ | Fan guard | **1. Detachment**<br>1) Perform work of item 1 of ① and 1 of ②.<br>**Requirement:**<br>**Perform the work on a corrugated cardboard, cloth, etc. to prevent scratches to the product.**<br>2) Remove the front cabinet, and place it down so that the fan guard side faces downwards.<br>3) Remove the hooking claws by pushing a minus screwdriver according to the arrow mark in the right figure, and remove the fan guard.<br>**2. Attachment**<br>1) Insert the claws of the fan guard in the hole of the front cabinet. Push the hooking claws (8 positions) by your hand and fix the claws.<br>**Requirement:**<br>**This completes all the attaching work. Check that all the hooking claws are fixed to the specified positions.** |  |

Downloaded from AC-Manual.com Manuals

| No. | Part name | Procedures | Remarks |
|---|---|---|---|
| ⑩ | Replacement of temperature sensor for servicing only<br><br>Common service parts of sensor TO, TS, TE, TD | 1) Cut the sensor 100 mm longer than old one.<br>2) Cut the protective tube after pulling out it (200 mm).<br>3) Move the protective tube toward the thermal sensor side and tear the tip of lead wire in two, then strip the covering part.<br>4) Pass the stripped part through the thermal constringent tube.<br>5) Cut the old sensor 100 mm length on the connector side, and recycle that connector.<br>6) Tear the lead wire in two on the connector side and strip and covering part.<br>7) Twist the leads on the connector and sensor sides, and solder them.<br>8) Move the thermal constringent tubes toward the soldered parts and heat them with the dryer and constring them.<br>9) Wind the attached color tape round the both terminals of the protective tube when colored protective tube is used.<br>10) Fix the sensor again.<br><br>**NOTES:**<br>1) Store the joint part of the sensor and the connector in the electric parts box.<br>2) Never joint them near the thermal sensor part. Otherwise, it would cause insulation inferiority because of dew drops.<br>3) When replacing the sensor using the colored protective tube, wind the color tape matching the color of that tube. |  |

These are parts for servicing sensors. Please check that the accessories shown in the right table are packed.

| | Part name | Q'ty | Remarks |
|---|---|---|---|
| 1 | Sensor | 1 | Length: 3 m |
| 2 | Sensor Spring (A) | 1 | For spare |
| 3 | Sensor Spring (B) | 1 | For spare |
| 4 | Thermal constringent tube | 3 | Including one spare |
| 5 | Color tape | 1 | 9 colors |
| 6 | Terminal | 3 | |

Downloaded from AC-Manual.com Manuals

# 13. EXPLODED VIEWS AND PARTS LIST

## 13-1. Indoor Unit (E-Parts Assy)




| Location No. | Part No. | Description |
|---|---|---|
| 401 | 43T60365 | TERMINAL BLOCK; 3P |
| 403 | 43T69319 | TEMPERATURE SENSOR |
| 404 | 43T69320 | TEMPERATURE SENSOR |

| Location No. | Part No. | Description |
|---|---|---|
| 405 | 43T69612 | PC BOARD ASSY ;WRS-LED |
| 410 | 43T62003 | CORD CLAMP |
| 411 | 43T69629 | ASM-PCB-SERV |

Downloaded from AC-Manual.com Manuals

## 13-2. Indoor Unit




| Location No. | Part No. | Description |
|---|---|---|
| 201 | 43T00479 | FRONT PANEL ASSY |
| 202 | 43T09405 | GRILLE OF AIR INLET (ORIGINAL) |
| 202 | 43T09407 | GRILLE OF AIR INLET (OPTIONAL;GRAY) |
| 203 | 43T03357 | BACK BODY ASSY |
| 204 | 43T80317 | AIR-FILTER |
| 205 | 43T09392 | HORIZONTAL LOUVER |
| 206 | 43T70313 | DRAIN-HOSE |
| 207 | 43T79301 | CAP-DRAIN |
| 208 | 43T21363 | MOTOR; STEPPING |
| 209 | 43T44387 | REFRIGERATION CYCLE ASSY |
| 210 | 43T47353 | PIPE; SUCTION (RAS-13) |
| 211 | 43T47355 | PIPE; SUCTION (U1U2_GD) |
| 212 | 43T11319 | PIPE SHIELD |

| Location No. | Part No. | Description |
|---|---|---|
| 213 | 43T19333 | FIX-PIPE-SENSOR |
| 217 | 43T22312 | ASM-BEAR-MOLD |
| 218 | 43T39323 | BEARING BASE |
| 219 | 43T20323 | ASSY CROSS FLOW FAN |
| 220 | 43T39324 | MOTOR BAND (LEFT) |
| 221 | 43T39321 | MOTOR BAND(RIGHT) |
| 222 | 43T21393 | FAN MOTOR |
| 224 | 43T82309 | INSTALLATION PLATE |
| 225 | 43T69618 | WIRELESS-REMOCO |
| 226 | 43T83003 | HOLDER; REMOTE CONTROLLER |
| 227 | 43T62326 | TERMINAL COVER |
| 228 | 43T60317 | CORD MOTOR LOUVER |
| 229 | 43T07311 | PIPE HOLDER |

Downloaded from AC-Manual.com Manuals

## 13-3. Outdoor Unit (38NYV025M, 38NYV025M-A)




| Location No. | Part No. | Description |
|---|---|---|
| 1 | 43T19334 | FAN GUARD |
| 2 | 43T20324 | PROPELLER FAN |
| 3 | 43T00482 | FRONT CABINET |
| 4 | 43T43403 | CONDENSOR ASSEMBLY |
| 5 | 43T62323 | TERMINAL COVER |
| 6 | 43T19336 | FIN GUARD |
| 7 | 43T47308 | CAPILLARY TUBE; 1.0 DIA |
| 8 | 43T46331 | VALVE;PACKED 9.52 DIA |
| 9 | 43T47332 | BONNET, 9.52 DIA |
| 10 | 43T46332 | VALVE;PACKED 6.35 DIA |
| 11 | 43T47331 | BONNET, 6.35 DIA |
| 12 | 43T21396 | FAN-MOTOR (MADE IN CHINA) |
| 13 | 43T47001 | NUT FLANGE |
| 14 | 43T19312 | HANDLE |

| Location No. | Part No. | Description |
|---|---|---|
| 15 | 43T49327 | CUSHION,RUBBER |
| 17 | 43T50316 | BIMETAL THERMO |
| 18 | 43T41358 | COMPRESSOR(Made in China) |
| 19 | 43T19337 | PACKED VALVE COVER |
| 20 | 43T00481 | UPPER CABINET |
| 21 | 43T00448 | FIXING PLATE VALVE |
| 22 | 43T42331 | BASE PLATE ASSEMBLY |
| 23 | 43T79305 | DRAIN NIPPLE |
| 24 | 43T46313 | REACTOR |
| 25 | 43T46333 | 4 WAY VALVE |
| 26 | 43T46334 | COIL-4WAY ASSEMBLY |
| 27 | 43T04303 | PARTITION |
| 28 | 43T39325 | MOTOR BASE |
| 29 | 43T39326 | MOTOR BASE CONNECTION PLATE |

Downloaded from AC-Manual.com Manuals

## 13-4. Outdoor Unit (E-Parts Assy)




| Location No. | Part No. | Description |
|---|---|---|
| 701 | 43T62320 | HEATSINK |
| 702 | 43T69620 | ASM-PCB-SERV |
| 703 | 43T60352 | TERMINAL BLOCK; 6P |
| 704 | 43T60326 | FUSE |

| Location No. | Part No. | Description |
|---|---|---|
| 705 | 43T60377 | TEMPERATURE SENSOR |
| 706 | 43T50304 | SENSOR;HEAT EXCHANGER |
| 707 | 43T62313 | BASE-PLATE-PC |
| 708 | 43T55325 | CAPACITOR; PLASTIC-FILM |

Downloaded from AC-Manual.com Manuals

Downloaded from AC-Manual.com Manuals